

InLine Interface Card 2x Serial 9 Pin PCIe (PCI-Express)

Gamintojas: **INLINE** · Modelis: **76619D** · EAN: **4043718333202** · Prekės kodas: **659582**



35,90 €

Kaina su PVM

Be PVM: **29,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: Serial



Aprašymas

Two serial RS-232 ports via PCIe: Ideal for connecting classic serial devices in modern systems – stable and reliable.

High flexibility thanks to broad protocol support: Supports various bit lengths, parity types and user-defined baud rates – for maximum compatibility.

ASIX AX99100 chipset for reliable communication: Professional data transfer with integrated flow control (hardware/software) and 256-byte FIFO.

Universally applicable thanks to low and full profile design: Suitable for servers, workstations or industrial PCs in flat housings.

Advanced power management features: Supports PCIe Power Management 1.2, remote wakeup and IrDA mode – ideal for continuous industrial use.

The InLine® interface card 76619D expands PCs and workstations with two serial RS-232 ports via PCIe. This solution is ideal for industrial, commercial or technical applications where RS-232 continues to play a key role – for example, for controlling machines, measuring devices, cash registers, modems or laboratory technology.

Equipped with the powerful ASIX AX99100 chipset, the card offers stable data communication at up to 115,200 bps. It supports both hardware and software flow control, various data formats (5 to 9 bits), all common parity options and freely definable baud rates.

Thanks to on-chip FIFO with 256 bytes in the transmit and receive path, loss-free transmission is guaranteed even in intensive applications. The card supports remote wake-up, PCI Power Management 1.2 and slow IrDA mode – a plus point for service and maintenance applications. With the included low-profile and full-profile bezels, the card can be flexibly adapted to different housing designs. Driver support is available for Windows XP and above and Linux kernel 2.6.x and above.

Chipset: ASIX AX99100
Interface: PCIe 2.0 x1
Connections: 2x 9-pin serial ports (RS-232)
Supports 5, 6, 7, 8, 9 bit data formats
Parity: even, odd, none, space, mark
Transfer rate: up to 115,200 bps
Supports hardware/software flow control
FIFO: 256 bytes send & receive buffer per port
Compatible with standard & low-profile chassis
Power Management 1.2, remote wakeup, IrDA mode
Operating systems: Windows XP or newer, Linux 2.6.x or higher
Operating temperature: 0° C – 55° C
Storage temperature: -40° C – 70° C
Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	Serial
Host interface gender	Male
Expansion card standard	PCIe 2.0
Serial ports quantity	2
Serial interface type	RS-232, 9-pin
Design	
Internal	Yes
Country of origin	China
Power	
Power management	Yes
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2

Server operating systems supported

Windows Server 2003, Windows Server 2007, Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022

Weight & dimensions

Width	120 mm
Depth	1.24 mm
Height	75 mm
Weight	2.5 kg

Packaging data

Package width	140 mm
Package depth	150 mm
Package height	30 mm
Package weight	46 g
Package volume	1000 cm ³

Other features

Dimensions (WxDxH)	120 x 1.24 x 75 mm
--------------------	--------------------