

InLine Interface Card, 2x PS/2, USB header connector, PCIe (PCI-Express)

Gamintojas: **INLINE** · Modelis: **76620P** · EAN: **4043718333561** · Prekės kodas: **659590**



53,91 €

Kaina su PVM

Be PVM: **44,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: PS2, USB 2.0 header - 9 pin
- ✓ 0.48 Gbit/s



Aprašymas

Retrofitting classic PS/2 peripherals via PCIe: Two PS/2 ports for keyboard and mouse – ideal for industrial and maintenance systems.

Expansion with internal USB 2.0 pin header: Practical for internal USB devices or front panel integration in modern PC systems.

Proven Moschip MCS9990 chipset: Stable signal processing with PCIe 1.1 support and integrated PHY – reliable in continuous operation.

Compatible with modern and older operating systems: Supports Windows 2000 and above as well as Linux from kernel 2.6.x – for long-term system planning.

Compact solution for low and standard profiles: Suitable for workstations, industrial PCs or servers – easy integration even in limited space.

The InLine® 76620P interface card expands existing PCs or industrial systems with two external PS/2 ports and an internal USB 2.0 pin header. This makes it particularly suitable for applications where classic input devices such as PS/2 keyboards or mice are still in use.

The integrated USB pin header allows the connection of internal USB devices – for example, for front panel connections, fan controllers or card readers. The optional 4-pin power connector provides additional power for USB devices.

The card is based on the Moschip MCS9990 chipset and supports PCI Express V1.1 (x1). Thanks to its broad compatibility, it is ideal for use in special

or service environments, such as industrial plants, test benches or IT restoration.

Drivers are available for Windows from version 2000 and Linux systems from kernel 2.6.x.

Chipset: Moschip MCS9990

Interface: PCI Express V1.1 x1

External connections: 2x PS/2 (mouse, keyboard)

Internal connections: 1x USB 2.0 pin header (9-pin), 1x power connector (4-pin)

USB transfer rates: 480 Mb/s, 12 Mb/s, 1.5 Mb/s

USB: Backward compatible with USB 1.1 and 1.0

Operating systems: Windows 2000 or newer, Linux from kernel 2.6.x

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	PS2, USB 2.0 header - 9 pin
Host interface gender	Male
Expansion card standard	PCIe 1.1
Design	
Internal	Yes
Country of origin	China
Features	
Data transfer rate (max)	0.48 Gbit/s
Power	
Supplementary power connectors	4-pin Molex
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Weight & dimensions	
Width	120 mm
Depth	1.18 mm

Height	100 mm
Weight	2 kg
Packaging data	
Mounting brackets included	Yes
Package width	140 mm
Package depth	150 mm
Package height	30 mm
Package weight	50 g
Other features	
Dimensions (WxDxH)	120 x 1.18 x 100 mm