

InLine 76625E interface cards/adapter Internal Parallel

Gamintojas: **INLINE** · Modelis: **76625E** · EAN: **4043718341405** · Prekės kodas: **659592**



31,90 €

Kaina su PVM

Be PVM: **26,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: Parallel
- ✓ 0.0015 Gbit/s



Aprašymas

Addition of a parallel DB25 port for connecting printers, scanners and other peripheral devices

PCIe x1 interface (compatible with x1, x4, x8 and x16 slots)

Bidirectional data transfer for efficient communication between devices

Supports SPP, EPP and ECP (IEEE 1284-compliant)

Low-profile format with low-profile slot bracket for compact systems

The **InLine® PCIe interface card** adds a powerful **25-pin parallel DB25 port** to your PC. It enables **reliable, bidirectional data transmission** and is ideal for connecting printers, scanners or other parallel port devices.

Thanks to the **PCI Express x1 interface (v1.1)**, the card is **compatible with x1, x4, x8 and x16 slots** and can be easily integrated into modern computer systems. The **256-byte FIFO buffer** ensures smooth and fast transfer with a data transfer rate of **up to 1.5 MB/s**.

Technical data:

Bus type & PCIe: PCIe v1.1 (2.5 GT/s) x1 lane (compatible with x1, x4, x8, x16 slots)

Connector: 1 x 25-pin parallel connector (DB25)

Chip set: WCH CH382L

Duplex mode: Bidirectional transmission

FIFO buffer: 256 bytes

Form factor: Low Profile

Dimensions: 85 mm x 60 mm (PCIe board)

Supported protocols & compatibility:

IEEE 1284 compliant, supports SPP, EPP and ECP

Data transfer rate:

Up to 1.5 MB/s - efficient, bidirectional LPT data transfer

Operating system support:

Windows: 11, 10, 8, 7, Vista, XP

Windows Server: 2003, 2008

Linux: from kernel version 2.4

Environmental conditions:

Operating temperature: 0 °C to 55 °C

Storage temperature: -40 °C to 70 °C

Maximum humidity: 90 %

Scope of delivery:

1x InLine® interface card, 1x parallel 25-pin, PCIe

1x low-profile slot bracket

1x driver CD

1x user manual (German/English)

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	Parallel
Host interface gender	Male
Expansion card form factor	Low-profile
Expansion card standard	PCIe 1.1
Parallel ports quantity	1

Design

Internal	Yes
Country of origin	Taiwan

Features

Chipset	WCH CH382L
Data transfer rate (max)	0.0015 Gbit/s
FIFO (First In, First Out)	256 B
Bidirectional	Yes

Operational conditions

Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	0 - 90%

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
Server operating systems supported	Windows Server 2003, Windows Server 2008

Technical details

Compliance certificates	CE, Federal Communications Commission (FCC), TÜV mark
-------------------------	---

Weight & dimensions

Width	85 mm
Depth	60 mm

Packaging data

Mounting brackets included	Yes
Drivers included	Yes
Manual	Yes
Package weight	40 g
Package type	Hanging box