

InLine 76660V interface cards/adapter Internal M.2

Gamintojas: **INLINE** · Modelis: **76660V** · EAN: **4043718341603** · Prekės kodas: **659599**



19,90 €

Kaina su PVM

Be PVM: **16,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: M.2
- ✓ NVMe
- ✓ 4 Gbit/s



Aprašymas

Supports an NVMe SSD (M.2 Key M) for fast memory expansion
PCIe 3.0 x4 interface with a maximum bandwidth of up to 32 Gb/s
Automatic lane detection on boot for easy system integration
Onboard LED indicator for displaying read and write activities
No additional drivers required – ready for immediate use

The **InLine® PCI Express card** enables the operation of a **NVMe SSD (M.2 Key M)** via a **PCIe 3.0 x4 interface** with up to **32 Gb/s bandwidth**, enabling fast boot times and optimized data transfers.

Thanks to **automatic lane detection during booting**, the card is easily integrated into the system. The **power supply of the NVMe SSD is provided directly via the PCIe bus (3.3 V)**. In addition, an **LED indicator** facilitates error diagnosis and shows the operating status of the SSD.

Technical data:

Bus type & PCIe: PCIe 3.0 x4 lane (maximum bandwidth up to 32 Gb/s)

Connection – interfaces:

1 x M.2 slot (Key M) for NVMe SSDs

Compatible module sizes: 2230, 2242, 2260, 2280

Data rate: Each port supports transfer rates of up to 4 Gb/s

Dimensions: 95 mm x 52 mm (PCIe board)

Operating conditions:

Operating temperature: -40 °C to +85 °C

Functions:

Automatic detection of the lane configuration at boot

Onboard LED indicator to display the read/write activity

NVMe SSD receives its power supply directly via the PCIe bus (3.3 V)

No additional driver required

System requirements:Hardware:

PC with a free PCIe slot (x4, x8 or x16 – the card is compatible)

Motherboard with support for PCIe 3.0 or higher

Operating system support:

Windows: 11, 10, 8.1, 8, 7

Windows Server: 2012 R2

Linux: from kernel 2.6

Scope of delivery:

1 x InLine® PCI Express card to 1x internal NVMe M.2

1 x low-profile slot bracket

1 x hand screwdriver

2 x screws

1 x heat conduction pad

1 x instruction manual (German/English)

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Ports & interfaces

Host interface

PCIe

Output interface	M.2
Host interface gender	Male
Expansion card standard	PCIe 3.0
NVMe	Yes
Number of M.2 (M) slots	1
Design	
Internal	Yes
LED indicators	Yes
Country of origin	Taiwan
Features	
Data transfer rate (max)	4 Gbit/s
Bandwidth	32 Gbit/s
Power	
Power supply input voltage	3.3 V
Operational conditions	
Operating temperature (T-T)	-40 - 85 °C
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 8, Windows 8.1
Linux operating systems supported	Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2, Linux Kernel 6.5
Server operating systems supported	Windows Server 2012 R2
Technical details	
Compliance certificates	TÜV mark, Federal Communications Commission (FCC), CE
Weight & dimensions	
Width	95 mm
Depth	52 mm
Weight	33 g
Packaging data	
Mounting brackets included	Yes
Manual	Yes
Package weight	33 g
Package type	Hanging box