

InLine 76661M interface cards/adapter Internal USB 3.2 Gen 1 (3.1 Gen 1), USB Type-C

Gamintojas: **INLINE** · Modelis: **76661M** · EAN: **4043718333691** · Prekės kodas: **659604**



62,90 €

Kaina su PVM

Be PVM: **51,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: USB 3.2 Gen 1 (3.1 Gen 1), USB Type-C
- ✓ 5 Gbit/s



Aprašymas

Triple USB expansion via PCIe: Two USB-A 3.2 Gen.1 ports and one USB-C port – ideal for mixed peripheral environments.

USB-C with Power Delivery 3.0: Up to 30 W charging power for smartphones, tablets and notebooks – right at your workstation.

High data rates up to 5 Gb/s: For fast file transfer and smooth operation of mass storage devices and USB devices.

6-pin PCIe power connector: Ensures stable power supply – even during intensive use.

Compatible with Windows & Linux: Broad system support, ideal for professional use in mixed infrastructures.

The InLine® 76661M interface card brings modern USB connectivity directly to your workstation, industrial PC or server environment. With two USB-A 3.2 Gen.1 ports and a full-featured USB-C port with Power Delivery 3.0 (30 W charging power), it is ideal for professional users with high demands on data transfer and power supply.

The USB-C port is not only suitable for data communication with modern devices such as docking stations, storage media or adapters – it also supplies power to power-intensive devices such as smartphones, tablets or ultrabooks. The two USB-A ports provide proven interfaces for classic USB peripherals.

The card is based on the stable VIA VL805 chipset, uses PCI Express V2.0 and is additionally powered via a 6-pin PCIe power connector to ensure stable voltage even under full port load.

It is compatible with all common operating systems from Windows XP and Linux from kernel 2.6.x. Ideal for technical workstations, media production, development environments or service providers who want to integrate modern USB technology into existing systems.

Chipset: VIA VL805

Interface: PCI Express V2.0

External connections: 2x USB-A 3.2 Gen.1, 1x USB-C 3.2 Gen.1 with PD3.0

Internal connection: 1x PCIe power (6-pin)

Data rates: 5 Gb/s, 480 Mb/s, 12 Mb/s, 1.5 Mb/s

Power: USB-C max. 30 W (20 V / 1.5 A), USB-A max. 4.5 W (5 V / 0.9 A)

Compatible operating systems: Windows XP or newer, Server 2008 R2 or newer, Linux from kernel 2.6.x

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	USB 3.2 Gen 1 (3.1 Gen 1), USB Type-C
Host interface gender	Male
Expansion card standard	PCIe 2.0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
Design	
Internal	Yes
Country of origin	China
Features	
Data transfer rate (max)	5 Gbit/s
Power	
Supplementary power connectors	1x 6-pin
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2

Server operating systems supported

Windows Server 2008 R2, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022

Weight & dimensions

Width120 mm

Depth1.36 mm

Height95 mm

Weight2 kg

Packaging data

Mounting brackets includedYes

Package width175 mm

Package depth150 mm

Package height30 mm

Package weight55 g

Other features

Dimensions (WxDxH)120 x 1.36 x 95 mm