

InLine 92501B wire connector Terminal block / D-Sub 9 Black, Green

Gamintojas: **INLINE** · Modelis: **92501B** · EAN: **4043718345861** · Prekės kodas: **659611**



18,90 €

Kaina su PVM

Be PVM: **15,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Terminal block / D-Sub 9 Male/Female
- ✓ 1 pc(s)
- ✓ Black, Green

Aprašymas

Time savings during installation: The spring-loaded terminals enable quick wiring with a flathead screwdriver (≤ 2.5 mm) – no soldering or crimping required.

Stable connection thanks to screw lock: The D-Sub 9 connector is equipped with an integrated screw lock and ensures a secure mechanical connection to the matching socket – even in the event of vibration or movement.

Versatile use in industry: Particularly suitable for automation, machine and plant engineering, service and test setups, and control cabinet construction.

Compact design: Saves space on DIN rails or in tight enclosures – ideal for integration into existing systems.

High signal quality: An insulation resistance of ≥ 10 M Ω and a rated current of 0.8 A per pin ensure reliable, low-interference signal transmission.

The **InLine® terminal block with D-Sub 9 connector** and integrated spring-cage terminal technology was specially developed for industrial applications that require serial signal transmission, e.g., via RS232. The tool-assisted spring-cage terminal technology allows quick and secure connection of individual wires without soldering or crimping. The connection range supports 14–22 AWG and can be conveniently operated with a flat-blade screwdriver ≤ 2.5 mm.

Thanks to the screw lock on the connector, a stable connection with mating sockets is guaranteed – even with movement or vibration. The compact design with EVA insulation on the underside protects against conductive surfaces during installation and makes the module ideal for use in control systems, machines, and test environments.

D-Sub 9 plug: With integrated screw lock

Spring terminals: 5 mm pitch

Connection range:14–22 AWG

Actuation:With flat-blade screwdriver ≤ 2.5 mm

Rated current:0.8 A per pin

Max. operating voltage:100 V between two signals

Insulation resistance:= 10 M Ω @ 300 V DC

Operating temperature:-10°C to +70°C

Insulation layer:EVA insulation on underside

Dimensions:approx. 51 x 31.5 x 18 mm (L x W x H)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Connector(s)	Terminal block / D-Sub 9
Product colour	Black, Green
Connector gender	Male/Female
Dielectric strength	300 V
Contact resistance	10 m Ω
Voltage	100 V
Current	0.8 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	31 x 51 x 18 mm
Weight	23 g
Width	31 mm
Depth	51 mm
Height	18 mm
Packaging data	
Quantity per pack	1 pc(s)
Package width	100 mm
Package depth	165 mm
Package height	20 mm
Package weight	26 g

Package volume	100 cm ³
----------------	---------------------

Package type	Polybag
--------------	---------

Logistics data

Country of origin	Taiwan
-------------------	--------