

InLine 92501C wire connector Terminal block / D-Sub 9 Black, Green

Gamintojas: **INLINE** · Modelis: **92501C** · EAN: **4043718345878** · Prekės kodas: **659612**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Terminal block / D-Sub 9 Female/Female
- ✓ 1 pc(s)
- ✓ Black, Green

Aprašymas

Time savings during installation: The screw terminals enable direct, field-ready wiring without additional adapters. Installation is tool-assisted with a flat-head screwdriver ≤ 2 mm. A connection range of 18–24 AWG is supported.

Stable connection thanks to screw lock: The D-Sub-9 female connector is equipped with an integrated screw lock and ensures a secure mechanical connection to the matching mating connector – even in the event of vibration or movement.

Versatile use in industry: Ideal for automation, machine and plant engineering, control cabinet installations, and mobile test and service applications.

Compact design: The terminal block can be easily integrated even in confined spaces – whether on a DIN rail or in mobile units.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1 A per pin ensure reliable signal transmission – even in continuous industrial applications.

The InLine® terminal block with D-Sub 9 socket and screw terminal connections offers a robust, field-ready solution for wiring serial signals – for example, in RS232 applications. The screw terminals with a 3.96 mm pitch allow single wires in the range of 18–24 AWG to be connected securely and permanently. Operation is carried out using a standard flat-blade screwdriver with a blade width of up to 2 mm.

The integrated screw lock on the socket ensures a stable connection to the mating connector – even under mechanical stress or vibration. The compact design and the insulating EVA layer on the underside enable secure integration, even on conductive mounting surfaces. This makes the terminal block ideal for industrial applications where reliability, space savings, and easy installation are required.

D-Sub 9 socket: With integrated screw lock

Connection technology: Screw terminal, grid dimension 3.96 mm

Connection range:18-24 AWG

Actuation:With flat-blade screwdriver ≤ 2 mm

Rated current:1 A per pin

Max. operating voltage:100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature:-10°C to +70°C

Insulation layer:EVA insulation on underside

Dimensions:approx. 38 x 37 x 16 mm (L x W x H)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Connector(s)	Terminal block / D-Sub 9
Product colour	Black, Green
Connector gender	Female/Female
Dielectric strength	300 V
Contact resistance	10 m Ω
Voltage	100 V
Current	1 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	37 x 38 x 16 mm
Weight	15 g
Width	37 mm
Depth	38 mm
Height	16 mm
Packaging data	
Quantity per pack	1 pc(s)
Package width	100 mm
Package depth	165 mm
Package height	17 mm
Package weight	17 g

Package volume	100 cm ³
Package type	Polybag
Logistics data	
Country of origin	Taiwan