

InLine 92501F wire connector Terminal block / D-Sub 9 Black, Green

Gamintojas: **INLINE** · Modelis: **92501F** · EAN: **4043718345908** · Prekės kodas: **659615**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Terminal block / D-Sub 9 Male/Female
- ✓ 1 pc(s)
- ✓ Black, Green



Aprašymas

Time savings during installation: Quick wiring via screw terminals for 12-22 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to screw lock: The D-Sub-9 plug is equipped with an integrated screw lock and ensures a secure mechanical connection to the matching socket – even in the event of vibration or movement.

Versatile use in industry: Ideal for automation, machine and plant engineering, control cabinet installations, and mobile test and service applications.

Compact, 2-row design: Measuring $45.5 \times 31 \times 16$ mm, the terminal block offers a space-saving arrangement – especially in dense wiring of Sub-D interfaces.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1 A per pin ensure reliable signal transmission – even in continuous industrial use.

The InLine® terminal block with D-Sub 9 connector in a 2-row design was developed for demanding industrial applications where space requirements and reliable wiring are equally important. Single wires in the range of 12-22 AWG can be securely connected via the screw terminals

with a 5.0 mm grid dimension. Installation is carried out using a standard flat-blade screwdriver ≤ 2.5 mm. The screw lock on the D-Sub connector ensures a stable connection to the mating socket – even with vibration or frequent unplugging. An EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces. This makes the connection block ideal for control cabinet construction, mobile test setups, or compact device installations.

D-Sub 9 connector: 2-row, with integrated screw lock
Connection technology: Screw terminal, grid dimension 5.0 mm
Connection range: 12–22 AWG
Actuation: With flat-blade screwdriver ≤ 2.5 mm
Rated current: 1 A per pin
Max. operating voltage: 100 V between two signals
Insulation resistance: ≥ 10 M Ω @ 300 V DC
Operating temperature: -10°C to $+70^{\circ}\text{C}$
Insulation layer: EVA insulation on underside
Dimensions: approx. 46 × 31 × 18 mm (L × W × H)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Connector(s)	Terminal block / D-Sub 9
Product colour	Black, Green
Connector gender	Male/Female
AWG wire size	12/22
Dielectric strength	300 V
Contact resistance	10 m Ω
Voltage	100 V
Current	1 A
Operational conditions	
Operating temperature (T-T)	$-10 - 70^{\circ}\text{C}$
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	31 x 46 x 18 mm
Weight	22 g
Width	31 mm
Depth	46 mm
Height	18 mm
Packaging data	

Quantity per pack	1 pc(s)
Package width	100 mm
Package depth	165 mm
Package height	18 mm
Package weight	24 g
Package volume	100 cm ³
Package type	Polybag
Logistics data	
Country of origin	Taiwan