

InLine 92505E wire connector RJ45 8P8C / Terminal block, 8-pin Black

 Gamintojas: **INLINE** · Modelis: **92505E** · EAN: **4043718346295** · Prekės kodas: **659649**


21,90 €

Kaina su PVM

 Be PVM: **18,10 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Female/Female Straight
- ✓ 1 pc(s)
- ✓ Black



Aprašymas

Push-in terminal for quick wiring: Single wires (18–26 AWG) are simply plugged in—no tools required. A flat-head screwdriver ≤ 2.5 mm is all you need to release them.

Standardized RJ45 socket for structured wiring: The 8P8C interface allows direct connection to network components – ideal for control, service, or test environments.

Compact design for space-critical applications: With a height of only 33 mm, the adapter also fits into flat housings, mounting rail slots, or mobile measuring devices.

Versatile use in industry: Ideal for control cabinet installations, embedded systems, machine networking, test environments, or rapid prototyping – without soldering or screws.

High signal quality: An insulation resistance of ≥ 10 MΩ at 300 V DC and a rated current of 1.0 A per pin ensure reliable and secure signal transmission – even under continuous load in industrial environments.

The InLine® RJ45 terminal block adapter with integrated push-in terminal enables tool-free connection of Ethernet signals (8P8C) with open wire

ends – ideal for industrial applications, laboratories, or test environments.

The permanently installed RJ45 socket (8-pin) is connected internally directly to a compact push-in terminal block. This allows quick connection of wires in the 18–26 AWG range – without any screws. A color-coded release button allows the connection to be released with a flat-head screwdriver ≤ 2.5 mm.

The compact design without additional mounting devices is particularly suitable for use in prototyping setups, diagnostic modules, embedded systems, or temporary test setups. The clearly marked connection area ensures safe and unambiguous signal assignment.

RJ45 interface: 8P8C socket (straight, shielded)

Terminal system: Push-in terminal (spring-loaded technology)

Number of poles: 8 signals (1:1 connected)

Connection range: 18–26 AWG (solid or stranded conductor with ferrule)

Actuation: Release with flat-blade screwdriver ≤ 2.5 mm

Rated current: 1.0 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10 °C to +70 °C

Insulation layer: EVA insulation on underside

Dimensions: approx. 33 x 28 x 21 mm (L x W x H)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Connector(s)	RJ45 8P8C / Terminal block, 8-pin
Product colour	Black
Connector gender	Female/Female
Connector form factor	Straight
AWG wire size	26/16
Dielectric strength	300 V
Contact resistance	10 m Ω
Current	1 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	28 x 33 x 21 mm
Weight	14 g
Width	28 mm
Depth	33 mm

Height	21 mm
--------	-------

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Package volume	100 cm ³
----------------	---------------------

Package type	Polybag
--------------	---------

Logistics data

Country of origin	Taiwan
-------------------	--------