

InLine 92505H wire connector RJ45 Cat.5e 8P8C / Terminal block, 8-pin Black

Gamintojas: **INLINE** · Modelis: **92505H** · EAN: **4043718346325** · Prekės kodas: **659652**



25,89 €

Kaina su PVM

Be PVM: **21,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Female/Female Straight
- ✓ Black
- ✓ 1 pc(s)



Aprašymas

Push-in terminal for quick wiring:Single wires (18–26 AWG) can be quickly plugged in – a flat-head screwdriver ≤ 2.5 mm is all you need to remove them.

Cat.5e RJ45 socket with fixed 15 cm connection cable:The shielded 8P8C socket is connected directly to the push-in terminal via a permanently integrated cable (length: 15 cm) – for flexible connections in confined spaces.

Space-saving cable solution for flexible integration:Thanks to its compact design and connected cable, the adapter is ideal for mobile measuring stations, embedded projects, or control cabinet installations.

Versatile use in industry:Perfect for temporary network connections, diagnostic tools, control systems, or prototyping – particularly suitable for changing test scenarios.

High signal quality:An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1.0 A per pin ensure reliable signal transmission – even in continuous industrial operation.

The InLine® RJ45 terminal block adapter with permanently integrated 15 cm cable and 8-pin push-in terminal connects structured Ethernet signals

(Cat.5e) with open wire ends – without soldering or screws. The shielded RJ45 socket (8P8C) is connected directly to the push-in terminal via a robust cable.

The push-in technology allows tool-free connection of wires in the 18–26 AWG range. If necessary, the connection can be disconnected using a flat-head screwdriver ≤ 2.5 mm via the color-coded buttons – ideal for frequent rewiring in test or prototype environments.

With a cable length of approx. 15 cm and an outer diameter of approx. 6 mm (shielded round cable), the adapter is also suitable for tight installation situations, e.g., in mobile test equipment or control cabinets. The shielded design and tested quality (short-circuit and wiring test) make it a robust solution for industrial networks and embedded applications.

- RJ45 interface:**Cat.5e, 8P8C socket (shielded)
- Cable length:**15 cm (Cat.5e, shielded, 4×2 wires, 24 AWG, flexible)
- Terminal system:**Push-in terminal (spring-loaded technology)
- Number of poles:**8 signals (1:1 connected)
- Connection range:**18–26 AWG (solid or stranded conductor with ferrule)
- Actuation:**Release with flat-head screwdriver ≤ 2.5 mm
- Rated current:**1.0 A per pin
- Max. operating voltage:**100 V between two signals
- Insulation resistance:** $\geq 10\text{ M}\Omega$ @ 300 V DC
- Operating temperature:**-10 °C to +70 °C
- Insulation layer:**EVA insulation on underside
- Dimensions without cable:**approx. 43 × 33 × 20 mm (L × W × H)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Connector(s)	RJ45 Cat.5e 8P8C / Terminal block, 8-pin
Product colour	Black
Connector gender	Female/Female
Connector form factor	Straight
AWG wire size	26/16
Dielectric strength	300 V
Contact resistance	10 mΩ
Current	1 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	28 x 320 x 16 mm
Cable length	0.15 m

Width	28 mm
Depth	320 mm
Height	16 mm
Packaging data	
Quantity per pack	1 pc(s)
Package volume	100 cm ³
Package type	Polybag
Logistics data	
Country of origin	Taiwan