

ATEN 2-Port USB - PS/2 VGA KVM Switch with Audio & USB 2.0 Hub (KVM Cables included)

Gamintojas: **ATEN** · Modelis: **CS1732B-AT-G** · EAN: **4710423775060** · Prekės kodas: **659667**



189,90 €

Kaina su PVM

Be PVM: **156,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality; 2048 x 1536; DDC2B
- ✓ Computer selection via front panel pushbuttons, multilingual OSD (On Screen Display), hotkeys and mouse
- ✓ Supports computers with PS/2 or USB keyboard and mouse configurations
- ✓ Video DynaSync™ - stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution



Aprašymas

The CS1732B is 2-port KVM switch combined with a 2-port USB 2.0 hub. As a KVM switch, it allows users to access two computers from a single keyboard, monitor, and mouse console. There are four methods to obtain instant access to any computer in your installation: Pushbuttons, Hotkeys, OSD, and mouse.

- 1 x CS1732B 2-Port USB 2.0 KVMP™ Switch
- 2 x 2L-5301U USB KVM Cables (1.2m)
- 1 x LIN5-04A2-J13G Firmware Upgrade Cable
- 1 x 0AD8-1605-24M1 Power Adapter
- 2 x OSD/Hotkey Stickers
- 1 x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	3.5mm headphone, 3.5mm mic
USB hub	Yes
USB 2.0 Type-A hub ports quantity	2
Audio connections	Yes
Headphone outputs	4
Number of microphone inputs	4
DC-in jack	Yes
Performance	
HD type	QXGA
Maximum resolution	2048 x 1536 pixels
Video bandwidth	60 Hz
Scan interval	1,255 s
DDC2B support	Yes
Firmware upgradeable	Yes
Design	
Product colour	Black, Metallic
Housing material	Metal
Cable length	1.2 m
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Display	
On Screen Display (OSD)	Yes
Power	
Power source	DC
Input voltage	5.3 V

Power consumption (typical)	2.5 W
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	140 mm
Depth	88 mm
Height	55.5 mm
Weight	1.15 kg
Packaging data	
Package width	62 mm
Package depth	283 mm
Package height	173 mm
Package weight	1.34 kg
Packaging content	
Cables included	KVM
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	11.5 kg
Harmonized System (HS) code	85176200
Master (outer) case width	335 mm
Master (outer) case length	582 mm
Master (outer) case height	195 mm
Master (outer) case gross weight	14.2 kg
Products per master (outer) case	10 pc(s)