

Zyxel EX3501-T0 wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) White

Gamintojas: ZYXEL · Modelis: EX3501-T0-EU01V2F · EAN: 4718937634767 · Prekės kodas: 660287



84,91 €

Kaina su PVM

Be PVM: 70,17 €

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 160 MHz in 5 GHz
- ✓ 2.4/5 GHz 2x2 ax
- ✓ EasyMesh standards
- ✓ TR-369/TR-069
- ✓ OPAL platform
- ✓ VoIP
- ✓ Comprehensive QoS



Aprašymas

Home office, gaming, and streaming compete for bandwidth, causing latency and buffering. The Zyxel EX3501/3500-T0 Series Dual-Band Wireless AX3000 Gigabit Ethernet IAD/Gateway, featuring Wi-Fi 6 (11ax) and Zyxel MPro Mesh® Solutions, optimizes bandwidth for superior connectivity and low latency. It is ideal for copper deployments and offers a budget-friendly transition to Wi-Fi 6 and Gigabit speeds.

Flexible and affordable Wi-Fi 6 with 160 MHz bandwidth

Say goodbye to buffering and hello to uninterrupted streaming, gaming, and browsing. The Series has advanced technology to ensure reliable connectivity with unmatched speed to your customers' devices.

MPro Mesh® kills the dead zones

Featuring EasyMesh fully compliant Zyxel MPro Mesh® Solutions, service providers can integrate with the Series to enhance your subscribers' experience by providing self-adapting, easy-to-manage whole-home Wi-Fi coverage, while reducing your service OPEX.

Remote management that reduces OPEX

Deploying a service technician is costly and time-consuming. Now you can configure, monitor, and troubleshoot devices without the expense of sending a service technician onsite.

Compliant with TR-069/TR-369 standard, the Series significantly simplifies deployment complexity and lowers operating and maintenance costs with its built-in remote management capabilities to reduce service time and stay ahead of the competition.

Superior flexibility and faster time-to-market with Zyxel OPAL firmware

The Series is available with Zyxel OPAL – our mature, modular software platform. The software incorporates a set of field-proven applications and allows you to easily manage your customer's premium services or seamlessly migrate and upgrade them to new technology – all with the advantage of reduced development time for you and great service for your customers.

You decide the QoS

Based on your service offerings to customers - you can freely define the QoS policies and prioritize mission-critical traffic such as Voice. Defining the QoS will improve your customer's network efficiency and give them the super-fast multi-play service quality they want.

Techninė specifikacija

Specifications	
Sandėlio grupė	[MDE] MODEMS [+10][-10]
WAN connection	
Ethernet WAN	Yes
SIM card slot	No
3G/4G USB modem compatibility	No
WAN connection type	RJ-45
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
WLAN data transfer rate (max)	2400 Mbit/s
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	600 Mbit/s
WLAN data transfer rate (second band)	2400 Mbit/s
Modulation	DTMF, OFDMA
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.1Q

Port forwarding	Yes
Automatic channel selection	Yes
Dynamic DNS (DDNS)	Yes
USB sharing	Yes
VPN Passthrough	Yes
PPPoE/PPTP/L2TP pass-through	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	4
USB port	Yes
USB 2.0 ports quantity	1
RJ-11 ports quantity	2
DC-in jack	Yes
Management features	
Wi-Fi Multimedia (WMM)/(WME)	Yes
Quality of Service (QoS) support	Yes
Reset button	Yes
WPS push button	Yes
MU-MIMO technology	Yes
Security	
Security algorithms	HTTPS, IPSec, SNMP, SNMPv2, WPA2-PSK, WPA3-SAE
Firewall	Yes
Stateful Packet Inspection (SPI)	Yes
DoS attack prevention	Yes
MAC address filtering	Yes
IGMP snooping	Yes
Network address translation (NAT)	Yes
Protocols	
DHCP server	Yes
Design	
Product type	Tabletop router
Product colour	White
LED indicators	DSL, LAN, Power, WPS
On/off switch	Yes
Certificates	

Compliance certificates	CE, RoHS, UKCA
Packaging content	
Cables included	LAN (RJ-45), Phone (RJ-11)
AC adapter included	Yes
Quick start guide	Yes
Antenna	
Antenna design	Internal
Antenna type	2x2
Features	
Firmware upgradeable	Yes
Power	
Power source type	DC
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	165 mm
Depth	170 mm
Height	30 mm
Weight	288 g
Packaging data	
Package width	171.5 mm
Package depth	186 mm
Package height	82.5 mm
Package weight	557 g
Number of products included	1 pc(s)
Matmenys ir svoris	
Matmenys (I × P × A)	19,00cm × 17,00cm × 9,00cm
Svoris	0,64kg