

Cudy GS1005PTS1 network switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: CUDY · Modelis: GS1005PTS1 · EAN: 6971690791704 · Prekės kodas: 661734



94,90 €

Kaina su PVM

Be PVM: 78,43 €

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4x GbE with 802.3at/af Mode A PoE
- ✓ 1x Uplink GbE + 1x Uplink SFP
- ✓ 120W Power Supply
- ✓ Extend On/Off, VLAN On/Off
- ✓ Watchdog On/Off
- ✓ PoE Max, PoE per Port LED
- ✓ 200×118×44 mm (7.87×4.65×1.73")



Aprašymas

Reliable PoE for 24/7 Consistent Operation

IEEE 802.3at/af with 60W Port Enhancement.

Port 1 delivers up to 60W and the other PoE ports delivers up to 30W of power, making it suitable for camera with heater, access points, IP cameras, digital signage, and most other PoE devices.

PoE Auto Recovery

Turn on the Watchdog function to monitor port activity. If a connected device freezes and stops transmitting data for 5 minutes, the Watchdog will automatically reboot the corresponding PoE port.

Streamlined PoE Management Loved by Installers

Built-In Modes for Practical Use Cases

VLAN Isolates Downlink Ports for Improved Safety

Turn on the VLAN mode to prevent client-side hacking, preventing sensitive data from leaking. The downlink clients will only be able to communicate with the uplink devices.

Extend for 250 m Transmission

For long-distance networking, enable the Extend mode to connect clients up to 250 meters away by limiting the port speed to 10 Mbps.

Exceptional Built-Quality for Stable Operation

Build Robust Systems with Outstanding EMC

Improves service reliability and reduces downtime caused by power surges and ESD.

ESD: Contact 6kV; Air 8kV

Surge: Power DM 2kV, CM 4kV; RJ45 CM 4kV

Shielded Ports. Solid Metal Casing.

Ensures stable operation with Ethernet ports shielded with nickel-plated copper alloy and robust SPCC metal casing.

Versatile Scenarios

Surveillance

Office Networking

Campuses Wi-Fi

Accesses and Signages

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Network > Switches [+2183][-1086]

Management features

Quality of Service (QoS) support Yes

Cloud-managed No

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity 5

Basic switching RJ-45 Ethernet ports type Gigabit Ethernet (10/100/1000)

SFP module slots quantity 1

Uplink ports quantity 1

Power connector AC-in jack

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-TX
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Cat7e, Cat8, Cat8.1
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Optical fiber	
Switching optical modules type	Gigabit Ethernet
Data transmission	
MAC address table	2048 entries
Switching capacity	12.5 Gbit/s
Forwarding rate	8.929 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9216
Packet buffer memory	0.125 MB
Security	
Password protection	Yes
Design	
Rack mounting	Yes
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, Power
Wall mountable	Yes
Performance	
Flash memory	8 MB
Plug and Play	Yes
Fanless	Yes
Mean time between failures (MTBF)	100000 h
Power	
Power source	AC
Power supply included	Yes

AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	1.25 A
Output voltage	52 V
Output current	1.25 A
Power consumption (max)	120 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	3
Power over Ethernet plus (PoE+) ports quantity	1
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	120 W
Other features	
Warranty period	1 year(s)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	200 mm
Depth	145 mm
Height	44 mm
Weight	645 g
Packaging content	
Cables included	AC
Manual	Yes
Packaging data	
Package type	Box
Package width	245 mm
Package depth	190 mm
Package height	60 mm
Package weight	952 g
Logistics data	

Master (outer) case net weight	19 kg
Country of origin	China
Master (outer) case width	505 mm
Master (outer) case length	320 mm
Master (outer) case height	402 mm
Products per master (outer) case	20 pc(s)