

APC SRTL5KRM2UI-HW nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 5 kVA 5000 W

Gamintojas: **APC** · Modelis: **SRTL5KRM2UI-HW** · EAN: **731304738015** · Prekės kodas: **661918**



9 635,90 €

Kaina su PVM

Be PVM: **7 963,55 €**

Sandėlyje



Prekė internetu

Nusenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 5 kVA 5000 W
- ✓ Signalų forma: Sinusas
- ✓ Ličio-jonų (Li-Ion) 180 V
- ✓ Stelažas Sidabras, Pilka



Aprašymas

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 5KVA on-line 2U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with Hardwired input and Hardwired 3-Wire output. It embeds Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS

has a 5-year warranty on the UPS and Lithium-ion battery.

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	5 kVA
Output power	5000 W
Waveform	Sine
Input operation voltage (min)	180 V
Input operation voltage (max)	275 V
Input frequency	40 - 70 Hz
Output operation voltage (max)	220 V
Surge energy rating	1260 J
Heat dissipation	931 BTU/h
Number of input phases	1
Number of output phases	1
Single-phase input voltage supported	230 V
Noise level	55 dB
Ports & interfaces	
AC outlet types	Hard Wire 3-wire (1PH + N + G)
Battery	
Battery replacement accessibility	End-user
Battery technology	Lithium-Ion (Li-Ion)
Battery voltage	180 V
Battery recharge time	1.5 h
Design	
Form factor	Rackmount
Product colour	Silver, Grey
Rack capacity	2U
International Protection (IP) code	IP20
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%

Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 15240 m
Technical details	
Packaging recycled materials	Recycled cardboard
Preferred mounting position	no preference
Sustainable packaging	No
SCIP number	5ee38369-4dfb-4636-ab65-b08aa3242891
Take-back system	No
Packaging without single use plastic	No
Certificates	
Waste Electrical and Electronic Equipment (WEEE) compliance	Yes
Compliance certificates	RoHS, REACH, WEEE
Certification	CE; UKCA; EN/IEC 62040-1
Weight & dimensions	
Width	432 mm
Depth	701 mm
Height	86 mm
Weight	29.2 kg
Packaging data	
Package width	585 mm
Package depth	984 mm
Package height	392 mm
Package weight	38.5 kg
Logistics data	
Customs product code (TARIC)	8504409590
Total carbon footprint (kg of CO2e)	8395.6203440278
Country of origin	Philippines
Warranty period	5 year(s)
Other features	
Output connection type	hard wire 3-wire (1P + N + E) for 1 zone(s)
Output voltage	230 V
Mounting	front; horizontal
Optimising energy efficiency	Energy efficient product

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Atitikties deklaracija](#)
- › [Vaizdo įrašas 1](#) youtube.com/watch?v=7ZNIH07YA2Q
- › [Vaizdo įrašas 2](#) youtube.com/watch?v=MuvboT8QWic

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

- › [Atitikties deklaracija](#)