

iiyama T1532MSC-B5AG POS monitorius 38,1 cm (15") 1024 x 768 pikseliai Lietimui jautrus ekranas

Gamintojas: **IIYAMA** · Modelis: **T1532MSC-B5AG** · EAN: **4948570115990** · Prekės kodas: **661921**



295,91 €

Kaina su PVM

Be PVM: **244,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

The ProLite T1532MSC 15" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The anti-glare coating helps to avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. The touch function remains unaffected even if the glass is scratched. A

solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

TOUCH TECHNOLOGY - CAPACITIVE

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.

AG COATING

The anti-glare coating is used in professional-grade displays to help avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. It also makes the screen less susceptible to dust, grease and dirt marks.

IP54

The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

SCRATCH RESISTANCE

Scratch resistance is essential for touch solutions used in public places and schools. This is achieved thanks to a glass overlay covering the screen. It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

Techninė specifikacija

Ekranas	
Ekranas įstrižainė	38,1 cm (15")
Ekranas rezoliucija	1024 x 768 pikseliai
Lietimui jautrus ekranas	Taip
Ekranas ryškumas	315 cd/m²
Pikselių žingsnis	0,297 x 0,297 mm
Kontrasto santykis (tipinis)	700:1
Reakcijos laikas	8 ms
Matymo kampas, horizontalus	170°
Matymo kampas, vertikalus	160°
Natūralus kraštinių santykis	4:3
Savybės	
Produkto spalva	Juoda

Palaikomos „Windows“ operacinės sistemos

Taip

Palaikoma operacinė sistema „Linux“

Taip

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)

0 - 40 °C

Darbo santykinės drėgmės diapazonas

20 - 80%

Sandėliavimo temperatūros norma (T-T)

-20 - 60 °C

Sandėliavimo santykinis drėgmės diapazonas

10 - 90%

Sertifikatai

Sertifikavimas


CB, CE, TÜV, CU, cULus, VCCI

Matmenys ir svoris

Svoris

6,14kg


Energijos efektyvumas ir ekologinis projektavimas



> Energijos etiketė

> Gaminio informacijos lapas

> EPREL duomenų bazė



Dokumentai ir vaizdo įrašai

> Naudojimo instrukcija

> Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeesterstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt