

Microconnect MC-USBCHDMI1 video cable adapter 1 m HDMI Type A (Standard) USB Type-C Black

Gamintojas: MICRO CONNECT · Modelis: MC-USBCHDMI1 · EAN: 5715063039137 · Prekės kodas: 661995



28,89 €

Kaina su PVM

Be PVM: 23,88 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Designed in Denmark
- ✓ Supports a resolution of up to 4K with a display refresh rate of up to 60Hz
- ✓ Data transfer rate of up to 18 Gbit/s
- ✓ Support DP ALT MODE
- ✓ Support of digital audio transmission in stereo
- ✓ Soft TPE Jacket



Aprašymas

This USB-C to HDMI cable lets you connect your USB Type-C (supporting DP Alt Mode) or Thunderbolt 3 device to an HDMI display. The display cable supports High Dynamic Range (HDR10) and provides sharper images with enhanced video.

The USB-C video converter cable is fully compatible with your HDMI 2.0b equipment, supporting resolutions up to 4K 60Hz (3840x2160) and bandwidths up to 18Gbps. The cable offers 4:4:4 chroma subsampling, so every pixel gets its own unique color. It's also backward compatible with earlier versions of HDMI.

With HDR support, you can enjoy lifelike images with increased contrast, brightness and colors and greater luminosity than standard digital imaging.

Techninė specifikacija

Specifications	
Sandėlio grupė	Energy Supply > USB-Kabel & Adapter [+242][-27]
Features	
Cable length	1 m
Connector 1	HDMI Type A (Standard)
Connector 2	USB Type-C
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
HDMI version	2
HDCP	Yes
HDCP version	2.2
High Dynamic Range (HDR) supported	Yes
Maximum resolution	4096 x 2160 pixels
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
Data transfer rate	18 Gbit/s
Bandwidth	18000 MB/s
3D	Yes
Cable material	Copper
Product colour	Black
Chipset	RTD2172
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	32
Colour sampling	4:4:4
Certificates	
Compliance certificates	RoHS
Certification	RoHS
Weight & dimensions	
Cable diameter	4.8 mm
Weight	20 g
Packaging data	

Package width	274 mm
Package depth	162 mm
Package height	21 mm
Package weight	50 g
Packaging content	
Quantity per pack	1 pc(s)
Logistics data	
Warranty period	25 year(s)