

Yealink WF50 WLAN 433 Mbit/s

Gamintojas: **YEALINK** · Modelis: **WF50** · EAN: **6938818302174** · Prekės kodas: **662313**



50,90 €

Kaina su PVM

Be PVM: **42,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compatible with Yealink SIP-T27G/T41S/T42S/T46S/T48S IP Phone (Version 84)
- ✓ Dual-Band Connectivity
- ✓ High Transmission Rate
- ✓ Interference Free
- ✓ Reliable Connection
- ✓ Easy to Use
- ✓ Plug and Play

Aprašymas

Yealink WF50 is a next-generation Wi-Fi USB Dongle, designed to allow users to select whether to connect to a 2.4GHz (150 Mbps) Wi-Fi network or a 5GHz (up to 433 Mbps) Wi-Fi network. With wireless connections transitting over the 5GHz band, users no longer need to worry about the interference from nearby wireless devices which may interfere with their wireless signal, guaranteeing high-quality connections perfect for establishing calls and HD video streaming.

This dynamic plug-and-play style USB device is equipped with WPA/WPA2 encryptions, providing your network with active defense against security threats. Besides, WF50 owns the ability to establish Wi-Fi connectivity easily, quickly, and reliably, so that users can optimally communicate, collaborate and more.

Yealink WF50 is compliant with IEEE 802.11a/b/g/n/ac standard, maximizing reliability and throughput.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Ports & interfaces

Connectivity technology	Wireless
Host interface	USB
Interface	WLAN
USB version	2
Network	
Maximum data transfer rate	433 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi	Yes
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Frequency range	2.4 - 5 GHz
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Security algorithms	WEP, WPA, WPA-PSK, WPA2, WPA2-Enterprise, WPA2-PSK
Design	
Internal	No
Product colour	Black
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	27 mm
Depth	52 mm
Height	8 mm
Weight	28 g
Logistics data	
Harmonized System (HS) code	85176990