

Fujitsu 2x1Gbit Cu Intel I350-T2 Internal Ethernet 1000 Mbit/s

Gamintojas: FUJITSU · Modelis: S26361-F4610-L502 · EAN: 4053026551786 · Prekės kodas: 662339



361,90 €

Kaina su PVM

Be PVM: 299,09 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1000 Mbit/s 10/100/1000BaseT(X)
- ✓ PCI Express 2.1 Ethernet
- ✓ Internal Component for: Server Chipset: Intel® I350-AM2

Aprašymas

PLAN CP 2x1Gbit Cu Intel ® I350-T2

Trust the network communication of the new Ethernet LAN adapter. The new Intel® I350-T2 Ethernet LAN Adapter, based on the latest Intel® 1GbE chip technology, offers two Gigabit Ethernet ports for 10/100/1000BaseT.

Virtualization support and Wake-on-LAN with selectable port are just some of the features from which you will benefit. Optimal support for your virtualization is provided by the support for Virtual Machine Device Queues (VMDq), Single Root I/O virtualization and sharing specification (SR-IOV). SR-IOV requires corresponding support in the system BIOS and in the operating system. PCI-SIG SR-IOV defines extensions of the PCI Express (PCIe) specification and enables PCI hardware resources to be shared with several system images or Virtual Machines.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Ports & interfaces

Connectivity technology

Wired

Host interface	PCI Express
Interface	Ethernet
Ethernet LAN (RJ-45) ports	2
PCI version	2.1
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.1as, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z
Ethernet LAN	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000BaseT(X)
Wake-on-LAN ready	Yes
Jumbo frames support	Yes
Supported network protocols	iSCSI
LAN controller	Intel® I350
Design	
Internal	Yes
Component for	Server
Chipset	Intel® I350-AM2
LED indicators	Yes
Power	
Power consumption (typical)	4.4 W
Operational conditions	
Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Logistics data	
Harmonized System (HS) code	85176990
Other features	
Flow control support	Yes