

ATEN 16-Port USB - HDMI KVM Switch with USB Peripheral port

Gamintojas: **ATEN** · Modelis: **CS17916** · EAN: **4719264641602** · Prekės kodas: **662367**



758,90 €

Kaina su PVM

Be PVM: **627,19 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cascadable to two levels–control up to 256 computers
- ✓ Multi-Display feature – stack up to eight CS17916 units and display video from up to eight monitors(dual display/triple display/quad display/multi-display)
- ✓ Video DynaSync™ – exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- ✓ Broadcast mode - operations simultaneously performed on all selected computers, software installation and upgrading, system wide shutdown, etc



Aprašymas

The CS17916 16-port USB HDMI KVM Switch is a multi-purpose appliance that consolidates access and control of up to 16 HDMI computers from a single USB keyboard, USB mouse, and monitor console.

1x CS17916 16-Port USB HDMI KVM Switch with Rack Mounting Kit

2x 2L-7D02UH Custom USB HDMI KVM Cable Sets (1.8m)

1x LIN5-04A2-J11G Firmware Upgrade Cable

1x LIN2-418K-E12G Power Cord

1x OAD8-8005-40MG Power Adaptor

1x Foot Pad Set (4 pcs)

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Ports & interfaces	
Number of computers controlled	16
Keyboard port type	USB
Mouse port type	USB
Video port type	HDMI
Console ports	3.5mm headphone, 3.5mm mic, HDMI, USB A
HDMI ports quantity	16
USB 2.0 Type-B ports quantity	16
USB hub	Yes
USB 2.0 Type-A hub ports quantity	2
Audio connections	Yes
Headphone outputs	17
Number of microphone inputs	1
DC-in jack	Yes
Performance	
HD type	WUXGA
Maximum resolution	1920 x 1200 pixels
Video bandwidth	60 Hz
Scan interval	1,5,255 s
Design	
Product colour	Black
Housing material	Metal
LED indicators	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	5 V
Power consumption (typical)	8.66 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	432.4 mm
Depth	257.2 mm
Height	44 mm
Weight	5.1 kg
Packaging data	
Package width	133 mm
Package depth	499 mm
Package height	324 mm
Package weight	5.68 kg
Packaging content	
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	15.3 kg
Harmonized System (HS) code	85176200
Master (outer) case width	427 mm
Master (outer) case length	519 mm
Master (outer) case height	348 mm
Master (outer) case gross weight	18.1 kg
Products per master (outer) case	3 pc(s)