

LevelOne TURING 26-Port L3 Lite Managed Gigabit Switch, 2 x SFP/RJ45 Combo

Gamintojas: **LEVELONE** · Modelis: **GEL-2681** · EAN: **4015867198940** · Prekės kodas: **663666**



487,90 €

Kaina su PVM

Be PVM: **403,22 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24 Gigabit ports and 2 Gigabit RJ45/SFP combo ports
- ✓ QoS control for traffic prioritization and bandwidth management
- ✓ DHCP Client/Server
- ✓ Supports IPv4/IPv6 network operation
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- ✓ IEEE 802.3ad LACP for auto port aggregation
- ✓ Supports VLAN (Port-based, Protocol-based, Private, Q-in-Q, Tag-based) and GVRP
- ✓ IEEE 802.1d/w/s Spanning Tree Protocol (STP) and port mirroring
- ✓ IP Multicast Filtering through IGMP Snooping V1 / V2 / V3



Aprašymas

GEL-2681 L3 Lite Managed Gigabit Switch is a next-generation Ethernet Switch offering full suite of L2 features, including advanced L3 features such as Static Route that delivers better cost performance and lower total cost of ownership in Enterprise networks via fiber or copper connections.

GEL-2681 provides high HW performance and environment flexibility for SMBs/ Enterprises.

GEL-2681 is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership. The embedded Device Managed System is designed to be extremely easy-to-use/manage/install IP Phone, IP Cam, or Wifi-AP for Enterprise Applications.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Management features	
Switch type	Managed
Switch layer	L3
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	24
Combo SFP ports quantity	2
Console port	RJ-45
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Flow control support	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
Cable length detection	Yes
VLAN support	Yes
Virtual LAN features	Private VLAN, Voice VLAN, Tagged VLAN, Port-based VLAN
Data transmission	
MAC address table	8000 entries
Switching capacity	52 Gbit/s
Forwarding rate	38.68 Mpps
Store-and-forward	Yes

Static route	Yes
Jumbo frames support	Yes
Jumbo frames	9600
Security	
DHCP features	DHCP server, DHCP snooping, DHCP relay, DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes
IGMP proxy	Yes
Security algorithms	802.1x RADIUS
SSH/SSL support	Yes
Loop protection	Yes
BPDU filtering/protection	Yes
Protocols	
Supported network protocols	IPv4/IPv6
GARP VLAN Registration Protocol (GVRP)	Yes
Design	
Rack mounting	Yes
Product colour	Black
Reset button	Yes
LED indicators	Activity, Link, Speed
Safety	LVD
Performance	
Internal memory	128 MB
Flash memory	32 MB
Firmware upgradeable	Yes
Buffer size	512 KB
Telnet	Yes
sFlow	Yes
Mean time between failures (MTBF)	463931 h
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	16.79 W
Power over Ethernet (PoE)	

Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-20 - 75 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Heat dissipation	73.87 BTU/h
Weight & dimensions	
Width	442 mm
Depth	211 mm
Height	44 mm
Weight	2.6 kg
Packaging content	
Cables included	AC, LAN (RJ-45)
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Resource CD	Yes
Package width	300 mm
Package depth	520 mm
Package height	90 mm
Package weight	3 kg
Certificates	
Certification	CE, FCC Part 15 Class A, VCCI, RoHS
Logistics data	
Country of origin	Taiwan
Master (outer) case width	482 mm
Master (outer) case length	540 mm
Master (outer) case height	324 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	16.2 kg
Products per master (outer) case	5 pc(s)