APC SMTL3000RMI2UC nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 3 kVA 2700 W 9 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMTL3000RMI2UC** · EAN: **731304643173** · Prekės kodas: **663701**



4 530,91 €

Kaina su PVM

Be PVM: **3 744,55 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ 9 AC išvestis(ys / čių)
- ✓ Ličio-jonų (Li-Ion)
- ✓ Stelažas Juoda, Pilka









Aprašymas

Stay always online and prevent data loss

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

Lithium-Ion

The APC SMTL3000RMI2UC uses a Li-Ion battery, which provides unique advantages:

- Longer lifespan. A Li-Ion battery can last up to 10 years and therefore makes the UPS truly maintenance-free.

- Can handle more than 10x as many charge cycles as a lead acid battery (VRLA).
- Smaller and lighter. Li-Ion batteries are smaller and weigh approximately 65% less than VRLA batteries, which saves space and simplifies installation.
- Better battery performance than VRLA at ambient temperatures above 25° C. With VRLA, this is at the expense of battery life (>5% decrease per degree increase).
- 5-year factory warranty. Standard long warranty on the UPS including the battery.
- Eliminate the costs of interim battery replacement; labor, material, shipping and recycling.
- Lower TCO: The above advantages reduce the total costs over the entire life of the UPS by up to 47% (compared to a UPS with VRLA battery.)
- Faster charging means full protection sooner.
- Perfect for tight spaces, due to the limited depth of the UPS it fits easily in wall racks and small cabinets.

SmartConnect

Out-of-box remote UPS monitoring, free for a 6-month trial period. Using the SmartConnect Ethernet port, you can easily connect the Smart-UPS to your network and monitor it remotely via the secure APC SmartConnect cloud-based web portal*. In addition, the UPS can always be monitored via this port via EcoStruxure IT Expert (SFTWES1-DIGI).

* Extend access to SmartConnect via the following licenses:
1 year Standard Plan: ERWPMON1-1Y-DIGI
3 year Standard Plan: ERWPMON1-3Y-DIGI

1 year Advanced Plan: ERWPLUS1-1Y-DIGI
3 year Advanced Plan: ERWPLUS1-3Y-DIGI

Network Management Card

If you connect the UPS directly to your network via the optional APC Network Management Card (AP9640/AP9641), it can be easily managed remotely via SNMP or our remote management software Ecostruxure IT Expert (SFTWES1-DIGI). You can also automatically send a shutdown signal via the network to multiple physical and/or virtual servers. By means of the APC PowerChute Network Shutdown Software belonging to the network card, the shutdown moment and the order in which this happens can even be differentiated.

Ease of use

By means of physical buttons and an LCD screen it is possible to set and read the basic functionalities.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. This way you can easily see how long the UPS will provide emergency power at a certain load.

Extend the lifespan

The internal battery cartridge (APCRBC174-LI) can be easily, safely and independently replaced by the user. This without having to switch off the APC UPS or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Mounting

The UPS is equipped with mounting brackets with which you can easily mount it to the 4 uprights in a 19 inch rack, wall or patch cabinet.

Warranty extension

The factory warranty of the SMTL3000RMI2UC is 5 years and can be extended with the APC service pack (WEXTWAR1YR-SPL-14) in steps of 1 year, up to a total maximum of 7 years.

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outlets and the equipment connected to them. If SmartConnect Advanced (ERWPLUS1-1Y-DIGI), a UPS with SmartConnect port + Ecostruxure IT Expert (SFTWES1-DIGI) or a network card (ap9640) in combination with Ecostruxure IT Expert (SFTWES1-DIGI) are used, this can even be done remotely.

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. The 3000VA line interactive 2U rackmount UPS provides pure sine wave power to support critical electronics during power disruptions. It comes with IEC 320 C14 input, 8x IEC 320 C13 and 1x IEC 320 C19 outlets. It offers cloud-based remote power monitoring, UPS firmware upgrades, remote diagnostics and proactive email notifications with recommended actions. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. It provides surge protection against lightning strikes, power sags, brownouts and surges. The SMTL UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	3 kVA
Išvesties galia	2700 W
Signalų forma	Sinusas
Įvesties eksploatacinė įtampa (min.)	160 V
Įvesties eksploatacinė įtampa (maks.)	286 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz

Viršįtampio energijos įvertinimas	739 J
Reakcijos laikas	6 ms
Amplitudės koeficientas	3:1
Avarinis elektros išjungimas (EPO)	Taip
Garso lygis	55 dB
Garsiniai perspėjimo signalai	Taip
Automatinis paleidimas iš naujo	Taip

Ryšys

AC išėjimo tipai	C13 šakotuvas, C19 šakotuvas
Maitinimo laido kištukas	C20 šakotuvas
Lizų kiekis	9 AC išvestis(ys / čių)
USB prievadas	Taip
Nuoseklioji sąsaja	Taip
Serijinių portų kiekis	1
Ethernet LAN (RJ-45) portų kiekis	1
„SmartSlot“	Taip
„SmartConnect“ prievadas	Taip

Baterija

Baterijos technologija	Ličio-jonų (Li-Ion)
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip

Konstrukcija

Forma	Stelažas
Produkto spalva	Juoda, Pilka
Rėmo pajėgumas	2U
Valdymo tipas	Jutiklinis
Ekrano tipas	LCD
LED indikatoriai	Taip
Tarptautinės apsaugos (IP) kodas	IP20

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Darbinis aukštis	0 - 3048 m
Ne darbinis aukštis	0 - 7620 m
Sertifikatai	
Atitikties sertifikatai	RoHS
Pakuotės turinys	
Stovo montavimo rinkinys	Taip
Pridėti kabeliai	RJ-45, USB laidas
Pridedama valdymo kortelė	Ne
Svoris ir matmenys	
Plotis	432 mm
Ilgis	683 mm
Aukštis	86 mm
Svoris	33,3 kg
Pakuotės duomenys	
Pakuotės plotis	600 mm
Pakuotės gylis	980 mm
Pakuotės aukštis	458 mm
Paketo svoris	41,5 kg
Kitos savybės	
Nominalioji išėjimo įtampa	230 V
Nominali įėjimo įtampa	230 V
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	102,00cm × 66,00cm × 60,00cm

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt