

ATEN 8-Port 17" LCD KVM Switch Over IP (USB - PS/2 VGA) with USB Peripheral port

Gamintojas: **ATEN** · Modelis: **CL5708IM-ATA-GG** · EAN: **4719264645600** · Prekės kodas: **663815**



1 565,90 €

Kaina su PVM

Be PVM: **1 294,13 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- ✓ Integrated KVM console with 17" or 19" LED-backlit LCD monitor in a Slideaway™ housing
- ✓ 1 remote bus for KVM over IP access-allowing IT administrators to remotely monitor and control upto 8 servers
- ✓ Mouse DynaSync™ -automatically synchronizes the local and remote mouse movements



Aprašymas

The CL5708I Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5708I can control up to 8 computers. As many as 15 additional KVM switches can be daisy chained to the CL5708I, so that up to 128 computers can all be controlled from a single KVM console.

TEST NOW!

1x CL5708I LCD KVM over IP Switch with standard Rack Mount Kit

2x 2L-5202U Custom KVM Cables (VGA, USB; 1.8 m/6 ft)

1x LIN5-27X6-U22G Custom Console Cable (VGA, USB, PS/2; 27 cm/0.88 ft)

1x LIN5-04A2-J11G Firmware Upgrade Cable

1x LIN2-418K-E12G Power Cord

1x User Instructions

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Display	
Display diagonal	43.2 cm (17")
Display	LCD
Technical details	
Product colour	Black
Operating relative humidity (H-H)	0 - 80%
Maximum resolution	1920 x 1200 pixels
Rack mounting	Yes
Number of computers controlled	1
LED indicators	Yes
Ports & interfaces	
VGA (D-Sub) ports quantity	8
Keyboard port type	USB
Mouse port type	USB
Video port type	VGA
Keyboard	
Keyboard language	US English
Keyboard layout	QWERTY
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	642.7 mm
Height	44 mm
Depth	480 mm
Weight	13.8 kg
Packaging data	
Package weight	16.7 kg
Package width	668 mm

Package depth	718 mm
---------------	--------

Package height	135 mm
----------------	--------

Packaging content

Quick installation guide	Yes
--------------------------	-----

Manual	Yes
--------	-----

Logistics data

Master (outer) case net weight	13.8 kg
--------------------------------	---------

Master (outer) case width	668 mm
---------------------------	--------

Master (outer) case length	718 mm
----------------------------	--------

Master (outer) case height	135 mm
----------------------------	--------

Master (outer) case gross weight	16.7 kg
----------------------------------	---------

Products per master (outer) case	1 pc(s)
----------------------------------	---------