

Canon EOS R100 + RF-S 18-45mm F4.5-6.3 IS STM Kit MILC 24.1 MP CMOS 6000 x 4000 pixels Black

Gamintojas: **CANON** · Modelis: **6052C013** · EAN: **4549292214598** · Prekės kodas: **664043**



581,90 €

Kaina su PVM

Be PVM: **480,91 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MILC 24.1 MP CMOS Black
- ✓ TTL Face tracking
- ✓ ISO sensitivity (min): 100 ISO sensitivity (max): 25600 Fastest camera shutter speed: 1/4000 s Slowest camera shutter speed: 30 s ± 3EV (1/3EV step)
- ✓ Video recording 3840 x 2160 pixels 4K Ultra HD
- ✓ Built-in microphone Built-in speaker(s) USB Type-C HDMI Bluetooth Wi-Fi
- ✓ Lithium-Ion (Li-Ion)



Techninė specifikacija

Specifications

Sandėlio grupė

Camera > Digitalkameras [+90][[-38]

Picture quality

Camera type

MILC

Megapixel (approx.)

24.1 MP

Sensor type	CMOS
Maximum image resolution	6000 x 4000 pixels
Still image resolution(s)	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600
Image stabilizer	No
Image formats supported	JPEG, Raw
Supported aspect ratios	1:1, 3:2, 4:3, 16:9
Image sensor size (W x H)	22.3 x 14.9 mm
Sensor format	Advanced Photo System type-C (APS-C)
Lens system	
Focal length range	18 - 45 mm
Minimum focal length (35mm film equiv)	29 mm
Maximum focal length (35mm film equiv)	72 mm
Minimum aperture number	32
Maximum aperture number	4.5
Lens structure (elements/groups)	7/7
Lens type	Standard zoom
Filter size	49 mm
Number of diaphragm blades	7
Lens mount interface	Canon RF
Focusing	
Focus	TTL
Focus adjustment	Auto/Manual
Auto focusing (AF) modes	Continuous Auto Focus, One Shot Focus, Servo Auto Focus
Auto Focus (AF) object detection	People
Face tracking	Yes
Auto Focus (AF) lock	Yes
Auto Focus (AF) assist beam	Yes
Exposure	
ISO sensitivity (min)	100
ISO sensitivity (max)	25600
Light exposure modes	Aperture priority AE, Auto, Manual, Shutter priority AE
Light exposure correction	± 3EV (1/3EV step)
Light metering	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot
ISO sensitivity	100, 6400, 12800

Light exposure control	Program AE
Auto Exposure (AE) lock	Yes
Number of measurement zones	384
Shutter	
Fastest camera shutter speed	1/4000 s
Slowest camera shutter speed	30 s
Camera shutter type	Electronic
Flash	
Flash exposure lock	Yes
Flash guide number	6 m
External flash connector	No
Flash exposure compensation	Yes
Flash exposure correction	±3EV (1/3 EV step)
Shoe mounting point	Yes
Shoe mounting point type	Hot shoe
Video	
Video recording	Yes
Maximum video resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Video resolutions	3840 x 2160,1920 x 1080,1280 x 720
Video formats supported	AVC, H.264, MP4, MPEG4
Audio	
Built-in microphone	Yes
Built-in speaker(s)	Yes
Audio system	stereo
Wind filter	Yes
Audio formats supported	LPCM, AAC
Memory	
Compatible memory cards	SD, SDHC, SDXC
Memory slots	1
Display	
Display	LCD
Touchscreen	No
Display diagonal	7.62 cm (3")

Display diagonal (metric)	7.5 cm
Display resolution	1040000 dot
Display aspect ratio	3:2
Vari-angle LCD display	No
Viewfinder	
Viewfinder type	Electronic
Magnification	0.95x
Viewfinder screen size	0.39"
Viewfinder frame rate (power saving mode)	30 fps
Viewfinder frame rate (smooth mode)	60 fps
Viewfinder resolution (approx.)	2360000 pixels
Ports & interfaces	
USB version	2
HDMI	Yes
USB connector	USB Type-C
HDMI connector type	Micro
Microphone in	Yes
Headphone connectivity	3.5 mm
Network	
Bluetooth	Yes
Wi-Fi	Yes
Bluetooth version	4.2
Bluetooth Low Energy (BLE)	Yes
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Camera	
White balance	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten
Scene modes	Children, Close-up (macro), Food, HDR backlight control, Handheld night scene, Landscape, Panning, Portrait, Silent shutter, Sports
Self-timer delay	2,10 s
Tripod mounting supported	Yes
Dioptrre correction	Yes
Histogram	Yes
Live view	Yes
Direct printing	Yes
GPS (satellite)	No

Orientation sensor	Yes
Anti-dust function	No
Smartphone/tablet remote support	Yes
View on smartphone	Yes
Image processor	DIGIC 8
Design	
Product colour	Black
Dustproof	No
Splash proof	No
Battery	
Battery technology	Lithium-Ion (Li-Ion)
Battery type	LP-E17
Number of batteries supported	1
Battery level indicator	Yes
Power	
USB Type-C charging port	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Weight & dimensions	
Width	116.3 mm
Depth	68.8 mm
Height	85.5 mm
Weight	309 g
Weight (including battery)	356 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	192 mm
Package depth	200 mm
Package height	154 mm
Package weight	1.11 kg
Packaging content	
AC adapter included	Yes
Neck strap included	Yes
Battery charger included	Yes

Batteries included	Yes
--------------------	-----

Logistics data

Products per pallet	144 pc(s)
---------------------	-----------

Matmenys ir svoris

Matmenys (l × P × A)	9,00cm × 15,00cm × 11,00cm
----------------------	----------------------------