

Zyxel USG FLEX 100AX hardware firewall 0.9 Gbit/s

Gamintojas: **ZYXEL** · Modelis: **USGFLEX100AX-EU0102F** · EAN: **4718937629473** · Prekės kodas: **664497**



980,90 €

Kaina su PVM

Be PVM: **810,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Firewall throughput: 900 Mbit/s
- ✓ 55.37 BTU/h
- ✓ 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
- ✓ Wireless
- ✓ 24.3 W



Aprašymas

The latest USG FLEX 100AX provides one single management platform on the cloud while expanding and strengthening the protection from firewalls to access points with automatic responses. The newly designed USG FLEX Series is capable of minimizing computing power usage and maximizing firewall performance, delivering up to 5x UTM performance with cloud flexibility and collaborative protection to help connect and secure small or mid-sized business users.

Nebula Together

USG FLEX firewalls, the new addition to the Nebula cloud management family, strongly empowers the full-blown Zyxel Security Matrix in Nebula, further optimizing Nebula with holistic security and protection for SMB business networks. Zyxel provides a centralized provisioning security policy to the remote workforce from Nebula and traffic shaping eliminating the network bottleneck to fuel the best business productivity.

Zero Trust

Networks Security

Remote working is here to stay, USG FLEX series applies the principles of zero trust access. It ensures the same security controls are applied to HQ, branch offices, home, or wherever your remote workers reside. Create access policy with device contextual such as OS version or device category to enforce network segmentation. This reduces the attack surface and prevents threats from spreading.

USG FLEX minimizes risk by adding granular policies and access authentication for the ever-growing needs of a secure workplace. Improve protection across identities, devices, applications, and network. Reduce risk and build trust across your entire digital assets.

High Assurance

Multi-layered Protection

USG FLEX is designed with multi-layer protection against multiple types of threats from in and out. Multiple security services empower you to restrict users' inappropriate application usage or web access. Zyxel offers leading-industry DNS content filter, eliminating blind spots in all encrypted traffic with TLS 1.3 without the need to deploy SSL inspection. All together safeguarding your network without any unattended gaps.

Simplified and Unified Licensing Experience

We know the experience from license purchase and renewals are equally important to our partners. We've optimized the licensing management platform and brought a consistent migration path between on-premise and our cloud platform. We make sure our partners can quickly adapt to a secure environment without the hassle but retaining the flexibility for those who need to practice the same security across networks scenarios.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server/Storage/Network > Access Points/Routers [+1151][-307]
Data transmission	
Firewall throughput	0.9 Gbit/s
VPN throughput	0.27 Gbit/s
IPS/IDS throughput	540 Mbit/s
Performance	
Heat dissipation	55.37 BTU/h
Antenna design	External
Antenna gain level (max)	3 dBi
Antennas quantity	2
Detachable antenna(s)	Yes
Network	
Wi-Fi	Yes
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
Number of VLANs	8
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Security	
VPN support	IKEv2, IPSec, SSL, L2TP/IPSec
Ports & interfaces	

Connectivity technology	Wireless
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Ethernet LAN (RJ-45) ports	4
WAN connection	Ethernet (RJ-45)
Power	
Input current	2.5 A
DC input voltage	12 V
Power consumption (max)	24.3 W
Certificates	
Compliance certificates	BSMI, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	216 mm
Depth	149.3 mm
Height	33 mm
Weight	1 kg
Packaging data	
Package width	284 mm
Package height	190 mm
Package depth	100 mm
Package weight	1.53 kg
Packaging content	
Cables included	Power
Other features	
Firewall throughput	900 Mbit/s
VPN throughput	270 Mbit/s