

Integral 250GB SSD 2.5INCH SATA 3 R-450MB/s W-400MB/s TBW 75 V SERIES 2

Gamintojas: **INTEGRAL** · Modelis: **INSSD250GS625V2** · EAN: **5055288447226** · Prekės kodas: **664613**



57,90 €

Kaina su PVM

Be PVM: **47,85 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2.5-inch form factor with SATA III 6Gbps interface (backward compatible with SATA 3Gbps and SATA 1.5Gbps)
- ✓ Performance: Faster boot than HDD, Faster access to applications, enhanced productivity and increased efficiency
- ✓ Non-volatile Flash Memory for outstanding data retention
- ✓ Ultra-efficient Block Management and Wear Levelling
- ✓ Supports S.M.A.R.T. - Self-Monitoring, Analysis and Reporting Technology
- ✓ 3 year warranty or TBW - whichever is earlier applies



Aprašymas

The Integral V Series SSD (V2) is an excellent choice for increasing storage and boosting performance for your desktop or laptop PC. With a fantastic combination of fast data read/write and reliability, along with low power operation, the Integral V Series offers excellent value.

Techninė specifikacija

Specifications

Sandėlio grupė

Components & Accessories > SSD [+1588][-1416]

Features

SSD capacity	250 GB
SSD form factor	2.5"
Interface	Serial ATA III
NVMe	No
Memory type	TLC
Component for	PC/Laptop
Hardware encryption	No
Data transfer rate	6 Gbit/s
Read speed	450 MB/s
Write speed	400 MB/s
Controller type	SMI SM2258XT
S.M.A.R.T. support	Yes
TRIM support	Yes
Mean time between failures (MTBF)	1500000 h
Protection features	Shock resistant
TBW rating	80
Certification	CE, FCC

Power

Operating voltage	5 V
Power consumption (read)	1.227 W
Power consumption (write)	1.584 W
Power consumption (idle)	0.4 W

Weight & dimensions

Width	69.8 mm
Depth	100.2 mm
Height	7 mm
Weight	45 g

Packaging data

Package width	108 mm
Package depth	135 mm
Package height	15 mm
Package weight	55 g
Package type	Box

Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 85%
Operating vibration	3.08 G
Non-operating vibration	3.08 G
Other features	
Compliance certificates	CE, Federal Communications Commission (FCC)