

Ubiquiti NanoBeam 5AC Gen 2 Network bridge 450 Mbit/s White

Gamintojas: **UBIQUITI** · Modelis: **NBE-5AC-GEN2** · EAN: **810354026348** · Prekės kodas: **665825**



111,90 €

Kaina su PVM

Be PVM: **92,48 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, IC, RoHS | PoE+ Injector(s): Yes | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Do not open the appliance, it does not contain serviceable parts. | Warnings: Keep the unit away from moisture and high temperatures. | Warnings: Use the appliance in accordance with its intended use to avoid risk of injury. | Operating temperature (T-T): -40 - 176 °F | Flash memory: 8 MB | Mounting type: Wall/Pole | Maximum transfer distance: 15000 m | Height: 125 mm | Internal memory: 128 MB | DC output current: 0.5 A | RAM type: DDR2 | Wi-Fi: Yes | Depth: 189 mm | Ethernet LAN: Yes | Mounting bracket(s) included: Yes | Harmonized System (HS) code: 85176990 | DC output voltage: 24 V | Product type: Network bridge | Surge protection: Yes | Modulation: 256-QAM | Power over Ethernet (PoE): Yes | Product colour: White | Modulation: 64-QAM | Modulation: 16-QAM | Modulation: BPSK | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): -40 - 80 °C | Modulation: QPSK | Processor family: Atheros | Weight: 530 g | Processor frequency: 720 MHz | Maximum data transfer rate: 450 Mbit/s | Ethernet LAN data rates: 1000 | Reset button: Yes | LED indicators: Signal strength | Web-based management: Yes | Power source type: PoE | Security algorithms: WPA2 | LED indicators: LAN | LED indicators: Power | Operating relative humidity (H-H): 5 - 95% | Frequency band: 5.15 - 5.875 5.15 - 5.25 5.25 - 5.35 5.47 - 5.725 5.725 - 5.85 GHz | Ethernet LAN data rates: 10 | Processor model: MIPS 74Kc | Power consumption (max): 8.5 W | Ethernet LAN data rates: 100 Mbit/s | Width: 189 mm | Ethernet LAN interface type: Gigabit Ethernet | Quantity per pack: 1 pc(s) | Material: Plastic | Antenna gain level (max): 19 dBi | Cables included: AC

Techninė specifikacija

Specifications

Sandėlio grupė

WISP [+10][-24]

Matmenys ir svoris

Matmenys (l × p × A)10,00cm × 22,00cm × 22,00cm

Svoris1,05kg