NET CAMERA P1487-LE BULLET/03183-001 AXIS

Gamintojas: **AXIS** · Modelis: **03183-001** · EAN: **7331021090330** · Prekės kodas: **666804**



1 217,90 €

Kaina su PVM

Be PVM: **1 006,53 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt





Aprašymas

This robust, cost-effective, AI-powered bullet camera delivers excellent 5 MP image quality in any light conditions. Built on ARTPEC-9, it supports AV1 codec and offers accelerated performance to run impressive analytics applications on the edge.

Outstanding image quality in any light
AXIS P1487-LE offers excellent image quality and forensic details in 5 MP at 60 fps, even in harsh weather and environments. It features OptimizedIR for surveillance in pitch darkness up to 50 m (164 ft). And Lightfinder 2.0 and Forensic WDR ensure true colors and great detail in near darkness or challenging light. Axis Zipstream with support for AV1, H.264, and H.265 significantly lowers bandwidth and storage requirements without compromising image quality. Furthermore, it features a 3-9 mm lens with a 106°-35° horizontal field of view for wide-area surveillance.

Robust with strong security
This impact-resistant, IK10-, IP66-, 67-, and NEMA 4X-rated outdoor-ready camera can handle extreme temperatures from -40°C to 60 °C (-40 to 140°F) and withstand winds up to 60 m/s (134 mph). It can be powered with DC and PoE for power redundancy. Axis Edge Vault, our hardware-based cybersecurity platform, safeguards the device and offers FIPS 140-3 Level 3 certified secure key storage and operation. In addition, electronic image stabilization provides smooth video in situations where a camera is subject to vibrations. What’s more, this robust camera is easy to install, maintain, and operate. For instance, it includes auto-rotation and remote zoom and focus.

Powerful analytics
Featuring a deep learning processing unit (DLPU), this AI-based camera runs advanced features and powerful analytics on the edge. For instance, it comes with AXIS Object Analytics preinstalled to detect, classify, track, and count humans, vehicles, and types of vehicles. With ARTPEC-9, this

application offers enhanced performance at greater distances. AXIS Image Health Analytics will notify you if the image is blocked, degraded, under-exposed, or redirected. And AXIS Live Privacy Shield addresses privacy laws and regulations and offers AI-based dynamic masking so you can detect movement and activities while safeguarding privacy.

- Excellent 5 MP video in any light
- Reduced storage costs with AV1 codec
- Next-generation AI-powered analytics
- Robust and impact-resistant
- Built-in cybersecurity with Axis Edge Vault

Summary: Axis P1487-LE. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Pole clamp, Product colour: White, Form factor: Bullet. Minimum illumination: 0.02 lx, Lens viewing angle, horizontal: 106 - 35°, Lens viewing angle, vertical: 77 - 26°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"). Focal length range: 3 - 8.5 mm | Vendor Homepage: https://www.axis.com/products/axis-p1487-le | Form factor: Bullet | Mounting type: Pole clamp | Product colour: White | LED indicators: Yes | Housing material: Aluminium/Polycarbonate (PC) | International Protection (IP) code: IP66, IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | PTZ control: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Alarm input/output: Yes | Built-in processor: Yes | Processor model: ARTPEC-9 | Dynamic range: 120 | Minimum illumination: 0.02 | Lens viewing angle, horizontal: 106 - 35 | Lens viewing angle, vertical: 77 - 26 | Camera pixel size: 2 | Camera shutter speed: 1/30500 - 2 | Number of sensors: 1 | Optical sensor size: 1/2.8 | Progressive scan: Yes | Sensor type: CMOS | Zoom capability: Yes | Focal length range: 3 - 8.5 | Auto focus: Yes | Maximum aperture number: 2.58 | Minimum aperture number: 1.36 | Night vision: Yes | Night vision distance: 50 | LED type: IR | Infra-red wavelength: 850 | Maximum resolution: 2592 x 1944 | Total megapixels: 5 | Video compression formats: AVI/H.264/H.265/M-JPEG | Video recording: Yes | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 2D noise reduction,3D noise reduction | Gain control type: Auto | Image quality adjustment: Brightness/Contrast/Saturation/Sharpness/White balance | Image stabilizer: Yes | Text caption overlay: Yes | Audio system: 2-way | Audio system full duplex: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet/Gigabit Ethernet | Networking standards: IEEE 802.1AE/IEEE 802.1ar/IEEE 802.1x/IEEE 802.3af/IEEE 802.3at | Wi-Fi: No | Bluetooth: No | Quality of Service (QoS) support: Yes | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Flash memory: 8192 | RAM capacity: 2048 | Ethernet LAN (RJ-45) ports: 1 | Microphone in: Yes | Terminal block port: Yes | DC-in jack: Yes | Network access storage (NAS): Yes | Pixel counter: Yes | Video motion detection: Yes | Cloud-managed: Yes | Power source type: DC,PoE | Power consumption (max): 12.95 | DC output voltage: 10,12,15,16,24,28 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 65 | Operating relative humidity (H-H): 10 - 100 | Storage relative humidity (H-H): 5 - 95 | Weight: 1370 | Number of cameras: 1 | Mounting kit: Yes | Manual: Yes | Unit Calculated Weight: 1.76 | Product Net Weight: 1 | Unit Calculated Volume: 0.007802 | Units per Shipping Box: 6 | Unit Width: 14.4 | Units per Pallet: 0 | Shipping Box Height: 28.5 | Unit Depth: 26.6 | Unit Height: 17.5 | Name: NET CAMERA P1487-LE BULLET/03183-001 AXIS | Model: P1487-LE

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	27,00cm × 14,00cm × 18,00cm