

NET CAMERA 5MP BULLET/HFW3549T1-ZASPV27135S5-B DAHUA

Gamintojas: **DAHUA** · Modelis: **HFW3549T1-ZASPV27135S5-B** · EAN: **6939554994265** · Prekės kodas: **666834**



601,90 €

Kaina su PVM

Be PVM: **497,44 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

Siren And Light Active Deterrence

Dahua siren and light active deterrence network camera supports the light alarm and voice alarm when perimeter event occurs, to realize the deterrence and effective intervention. The camera is built in multiple voices for selection, and supports customized voice importing.

Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the warm light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the warm light is off and the IR illuminator is on, which reduces light pollution efficiently.

SMD 4.0

Dahua Smart Motion Detection technology works with intelligent algorithms to classify targets that trigger motion detection alarms. It filters out objects that are not targets, such as small and large animals, to avoid triggering false alarms. With an AI NVR, Quick Pick technology becomes available, allowing you to easily search for and pick out human and vehicle targets from SMD event videos, prioritizing the highest matches.

One-tap Disarming

Dahua One-tap Disarming function, which is convenient and easy for operation, is the switch for event linkage. Customers can close and recover event linkage through mobile App, which meets multi-scenarios needs.

Cyber Security

Dahua network cameras employ a series of security technologies, including security authentication and authorization, access control protocols, trusted protection, encrypted transmission and encrypted storage. These technologies improve the camera's defense against external cyber threats and prevent malicious programs from compromising the device.

Protection (IP67, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes. Wide voltage: The camera allows $\pm 30\%$ input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

- 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- Outputs max. 5 MP (2960 × 1668) @20 fps and supports 4 MP (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in warm light and IR LED; the max. IR illumination distance is 50 m and warm light distance is 40 m
- ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk
- 12 VDC/PoE power supply
- IP67 protection
- Sound and light alarm (red and blue lights)
- SMD 4.0
- One-tap arming/disarming through alarm input

Summary: Dahua Technology WizSense IPC-HFW3549T1-ZAS-PV. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Bullet. Minimum illumination: 0.0003 lx, Lens viewing angle, horizontal: 113 - 36°, Lens viewing angle, vertical: 57 - 20°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Focal length range: 2.7 - 13.5 mm, Detect distance (wide): 65.2 m, Detect distance (tele): 186.6 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/3-Series/TiOC/IPC-HFW3549T1-ZAS-PV=S5> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: Black | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Certification: CE-LVD: EN 62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B; UL/CUL:UL62368-1 & CAN/CSA C22.2 No. 62368-1-14 | Camera pan control: No | Camera tilt control: No | Minimum illumination: 0.0003 | Lens viewing angle, horizontal: 113 - 36 | Lens viewing angle, vertical: 57 - 20 | Lens viewing angle, diagonal: 137 - 40 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Lamp/Manual/Outdoor | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of Privacy masking areas: 4 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Focal length range: 2.7 - 13.5 | Detect distance (tele): 186.6 | Detect distance (wide): 65.2 | Observe distance (tele): 37.3 | Observe distance (wide): 26.1 | Night vision: Yes | Night vision distance: 30 | Maximum resolution: 2592 x 1944 | Total megapixels: 5 | Video compression formats: H.264/H.264B/H.264H/H.265 | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2592 x 1944/2688 x 1520/640 x 480 (VGA) | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Privacy masking: Yes | Built-in speaker(s): Yes | Audio system: 2-way | Audio input channels: 2.0 | Audio output channels: 2.0 | Audio formats supported: G.711/G.726 | Built-in microphone: Yes | Audio detection: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet/Gigabit Ethernet | Wi-Fi: No | Bluetooth: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 512 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 2 | Alarm output channels: 2 | Mirror: Yes | Web-based management: Yes | Web browser: Yes | Power source type: DC,PoE | Power consumption (typical): 3.3 | Power consumption (max): 7.4 | Power consumption (Power over Ethernet (PoE)): 8.7 | DC output voltage: 12 | Operating temperature

(T-T): -30 - 60 | Storage temperature (T-T): -30 - 60 | Mobile operating systems supported: Android/iOS | Width: 94.4 | Depth: 288.4 | Height: 84.7 | Weight: 1050 | Package weight: 1350 | Unit Calculated Weight: 1.38 | Product Net Weight: 1.05 | Unit Calculated Volume: 0.00844 | Units per Shipping Box: 8 | Unit Width: 14.5 | Units per Pallet: 0 | Shipping Box Height: 32.8 | Unit Depth: 34 | Unit Height: 13.5 | Name: NET CAMERA 5MP BULLET/HFW3549T1-ZASPV27135S5-B DAHUA | Model: HFW3549T1-ZASPV27135S5-B

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Matmenys ir svoris	
Matmenys (l × p × A)	34,00cm × 15,00cm × 14,00cm