

NET CAMERA 4MP IR BULLET/IPC-HFW5442E-ZE-2712-S3 DAHUA

Gamintojas: **DAHUA** · Modelis: **IPC-HFW5442E-ZE-2712-S3** · EAN: **6923172587251** · Prekės kodas: **666849**



554,91 €

Kaina su PVM

Be PVM: **458,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

- Outputs max. 4MP (2688×1520) @25/30 fps
- Built-in IR LED, and the max. illumination distance is 60 m
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc
- Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 512 GB Micro SD card, built-in MIC
- 12 VDC/PoE power supply; ePoE
- IP67 and IK10 protection
- SMD 3.0

Summary: Dahua Technology Pro DH-IPC-HFW5442EP-ZE-2712-S3. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 115 - 47°, Lens viewing angle, vertical: 62 - 27°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"), Number of effective pixels (H x V): 2688 x 1520 pixels. Focal length range: 2.7 - 12 mm, Detect distance (wide): 57.5 m, Detect distance (tele): 130.8 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizMind-S-Series/4MP/IPC-HFW5442E-ZE=S3> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Dynamic range: 140 | Minimum illumination: 0 | Angle of rotation: 360 | Lens viewing angle, horizontal: 115 - 47 | Lens

viewing angle, vertical: 62 - 27 | Lens viewing angle, diagonal: 137 - 54 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of Privacy masking areas: 8 | Number of sensors: 1 | Optical sensor size: 1/1.8 | Progressive scan: Yes | Number of effective pixels (H x V): 2688 x 1520 | Sensor type: CMOS | Focal length range: 2.7 - 12 | Maximum aperture number: 1.8 | Closest focusing distance: 1.5 | Detect distance (tele): 130.8 | Detect distance (wide): 57.5 | Identify distance (tele): 13.1 | Identify distance (wide): 5.8 | Observe distance (tele): 52.3 | Observe distance (wide): 23 | Recognize distance (tele): 26.2 | Recognize distance (wide): 52.3 | Night vision: Yes | Night vision distance: 60 | LED type: IR | Number of illumination LEDs: 4 | Maximum resolution: 2688 x 1520 | Total megapixels: 4 | Video compression formats: H.264/H.264+/H.265/H.265+/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2688 x 1520/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: 32- 8192Kbps, 19- 8192Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: AAC | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP;SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP;QoS; UPnP;NTP | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast/Unicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 1024 | ROM capacity: 4000 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 2 | Alarm output channels: 1 | Mirror: Yes | Video motion detection: Yes | Web-based management: Yes | Power source type: DC,PoE | Power consumption (max): 9.9 | Power consumption (Power over Ethernet (PoE)): 10.9 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): 5 - 40 | Operating relative humidity (H-H): 10 - 95 | Storage relative humidity (H-H): 10 - 95 | Mobile operating systems supported: Android/iOS | Width: 95 | Depth: 95 | Length: 273.2 | Weight: 1120 | Package weight: 1660 | Number of cameras: 1 | Unit Calculated Weight: 1.59 | Product Net Weight: 1.12 | Unit Calculated Volume: 0.00777 | Units per Shipping Box: 1 | Unit Width: 15 | Shipping Box Height: 14 | Unit Depth: 37 | Unit Height: 14 | Name: NET CAMERA 4MP IR BULLET/IPC-HFW5442E-ZE-2712-S3 DAHUA | Model: IPC-HFW5442E-ZE-2712-S3

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Matmenys ir svoris	
Matmenys (l × p × A)	37,00cm × 15,00cm × 14,00cm