

NET CAMERA 5MP EYEBALL/IPC-HDW5559T-ZE-IL-27135 DAHUA

Gamintojas: **DAHUA** · Modelis: **IPC-HDW5559T-ZE-IL-27135** · EAN: **6937552412071** · Prekės kodas: **666858**



529,90 €

Kaina su PVM

Be PVM: **437,93 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

- High-Quality Imaging with 5MP Resolution
- Xinghan Vision Models: Comprehensive Enhancement of Target Detection, Imaging
- Longer Detection Distance with Xinghan Vision Models
- Supports Over 7 AI Functions, Applicable for Multi-scenario Targets Detection and Analysis
- Built-in Mic for Real-Time Audio Security

Summary: Dahua Technology IPC-HDW5559T-ZE-IL. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0005 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 110 - 32. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Fixed focal length: 2.8 mm, Detect distance (wide): 65.4 m, Detect distance (tele): 202 m | Vendor Homepage: <https://www.dahuasecurity.com/products/network-products/network-cameras/wizmind-5-series/smart-dual-light/5mp/ipc-hdw5559t-ze-il> | Form factor: Turret | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Metal | Protection features: Dustproof/Waterproof | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | People counting function: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Built-in light: Yes | Dynamic range: 120 | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.0005 | Angle of rotation: 360 | Lens viewing angle, horizontal: 110 - 32 | Lens viewing angle, vertical: 57 - 18 | Lens viewing angle, diagonal: 134 - 37 | Tilt angle range: 0 - 78 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter speed: 1/3 - 1/100000 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Maximum aperture number: 1.6 | Closest focusing distance: 0.3 | Detect distance (tele): 202 | Detect distance (wide): 65.4 | Fixed focal length: 2.8 | Identify distance (tele): 20.2 | Identify distance (wide): 6.5 | Observe distance (tele): 80.8 | Observe distance (wide): 26.1 | Recognize distance (tele): 40.4 | Recognize distance (wide): 13.1 | Night vision: Yes | Night vision distance: 50 | LED type: IR | Maximum resolution:

2960 x 1668 | Total megapixels: 5 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR),Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Audio formats supported: G.711 μ-law/G.711 A-law/G.723/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x/IEEE 802.3at | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P; Auto Registration | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | ROM capacity: 4000 | RAM capacity: 2000 | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Digital watermark: Yes | HTTPS encryption: Yes | Human and vehicle targets classification: Yes | Intelligent Video Surveillance (IVS) system features: Intrusion/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Power source type: DC | Power consumption (typical): 6.6 | Power consumption (max): 15.2 | Power consumption (Power over Ethernet (PoE)): 15.9 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Diameter: 122 | Length: 108.3 | Weight: 700 | Compliance certificates: CE | Package weight: 960 | Number of cameras: 1 | Manual: Yes | Lens type: Varifocal | Unit Calculated Weight: 0.92 | Product Net Weight: 0.7 | Unit Calculated Volume: 0.003456 | Units per Shipping Box: 1 | Unit Width: 16 | Units per Pallet: 0 | Shipping Box Height: 13.5 | Unit Depth: 16 | Unit Height: 13.5 | Name: NET CAMERA 5MP EYEBALL/IPC-HDW5559T-ZE-IL-27135 DAHUA

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 16,00cm × 14,00cm