

NET CAMERA 8MP BULLET/HFW3849T-ZAS-IL-27135-B DAHUA

Gamintojas: **DAHUA** · Modelis: **IPC-HFW3849T-ZAS-IL-27135-BLACK** · EAN: **6939554927171** · Prekės kodas: **666860**



521,90 €

Kaina su PVM

Be PVM: **431,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

With advanced deep learning algorithm, Dahua WizSense 3 Series network camera supports intelligent functions, such as perimeter protection and smart motion detection. With starlight technology, this series camera provides a better image effect in the condition of low illuminance

- High-Quality Imaging with 8 MP Resolution
- Motorized Varifocal Lens for Easy Installation and Monitoring
- Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- Enhanced Deep Learning-Based Human and Vehicle Classification
- Xinghan Vision Models: Comprehensive Enhancement of Target Detection, Imaging
- AcuPick Enables Fast and Precise Human&Vehicle Search
- Built-in Mic for Real-Time Audio Security
- IP67 for Protection Against Harsh Environments

Summary: Dahua Technology WizSense IPC-HFW3849T-ZAS-IL. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 114 - 32°, Lens viewing angle, vertical: 58 - 17°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Focal length range: 2.7 - 13.5 mm, Focus: Motorized/Manual, Detect distance (wide): 85.3 m | Vendor Homepage: <https://www.dahuasecurity.com/products/network-products/network->

cameras/WizSense-Series/3-Series/Smart-Dual-Light/IPC-HFW3849T-ZAS-IL | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: Black | Housing material: Metal | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Built-in light: Yes | Dynamic range: 120 | Minimum illumination: 0 | Angle of rotation: 360 | Lens viewing angle, horizontal: 114 - 32 | Lens viewing angle, vertical: 58 - 17 | Lens viewing angle, diagonal: 138 - 36 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Number of Privacy masking areas: 8 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Focal length range: 2.7 - 13.5 | Focus: Motorized/Manual | Maximum aperture number: 1.4 | Closest focusing distance: 0.1 | Detect distance (tele): 280 | Detect distance (wide): 85.3 | Identify distance (tele): 28 | Identify distance (wide): 8.5 | Observe distance (tele): 112 | Observe distance (wide): 34 | Recognize distance (tele): 56 | Recognize distance (wide): 17.1 | Night vision: Yes | Night vision distance: 60 | B/W night vision distance: 60 | Colour night vision distance: 60 | LED type: IR/White | Number of illumination LEDs: 4 | Maximum resolution: 3840 x 2160 | Total megapixels: 8 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto | Back Light Compensation (BLC): Yes | Bit rate control: Variable Bit Rate (VBR), Constant Bit Rate (CBR) | Flip & mirror: Yes | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio system: 1-way | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: G.711 µ-law/G.711 A-law/G.723/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Voice codecs: G.711a/G.711Mu/G.723/G.726/PCM | Ethernet LAN: Yes | Networking standards: IEEE 802.1x/IEEE 802.3af | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P | Number of users: 20 | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 512 | ROM capacity: 256 | RAM capacity: 1000 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | HTTPS encryption: Yes | Intelligent Video Surveillance (IVS) system features: Face detection/Intrusion/Tripwire/Vehicle detection | Video motion detection: Yes | Web browser: Yes | Cloud-managed: Yes | Cloud services supported: FTP | Power source type: PoE, DC | Power consumption (typical): 3.8 | Power consumption (max): 9.9 | Power consumption (Power over Ethernet (PoE)): 5.3 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Width: 90.7 | Depth: 238.5 | Height: 90.7 | Weight: 835 | Package weight: 1090 | Number of cameras: 1 | Lens type: Varifocal | Number of video streams: 3 | Unit Calculated Weight: 1.17 | Product Net Weight: 0.835 | Unit Calculated Volume: 0.00475 | Units per Shipping Box: 10 | Unit Width: 12 | Units per Pallet: 0 | Shipping Box Height: 26 | Unit Depth: 30 | Unit Height: 11 | Name: NET CAMERA 8MP BULLET/HFW3849T-ZAS-IL-27135-B DAHUA

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+144][-361]

Matmenys ir svoris

Matmenys (I × P × A)

30,00cm × 12,00cm × 11,00cm