

Dahua Technology WizSense IPC-HDBW3841R-ZAS-S2 Dome CCTV security camera Indoor & outdoor 3840 x 2160 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **IPC-HDBW3841R-ZAS27135S2** · EAN: **6923172542328** · Prekės kodas: **666867**



509,89 €

Kaina su PVM

Be PVM: **421,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8-MP 1/2.8" CMOS image sensor, excellent low luminance performance and high definition of images
- ✓ Outputs max. 8MP (3840 × 2160) @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED, max. IR distance: 40 m
- ✓ ROI, SMART H.264 +/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); max. 256 G Micro SD card; built-in Mic
- ✓ 12 VDC/PoE power supply facilitates installation



Aprašymas

8MP IR Vari-focal Dome WizSense Network Camera

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Performance	
Type	CCTV security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B; UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Camera	
Angle of rotation	355°
Tilt angle range	0 - 75°
Pan range	0 - 355°
White balance	Auto, Custom modes, Lamp, Manual, Natural, Outdoor
Camera shutter type	Electronic
Camera shutter speed	1/100000 s
Adjustment shutter speed	Auto/Manual
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Lens system	
Number of lenses	1
Focal length range	2.7 - 13.5 mm

Fixed focus	Yes
Maximum aperture number	1.5
Detect distance (wide)	85.3 m
Detect distance (tele)	280 m
Observe distance (wide)	34.1 m
Observe distance (tele)	112 m
Recognize distance (wide)	17 m
Recognize distance (tele)	56 m
Identify distance (wide)	8.5 m
Identify distance (tele)	28 m
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	40 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.265
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2592 x 1944, 2688 x 1520, 3072 x 1728, 3072 x 2048, 3840 x 2160
Analog signal format system	NTSC
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
Audio	
Audio input channels	1.0 channels

Audio output channels	1.0 channels
Audio formats supported	G.711 A-law, G.711 μ -law, G.726
Signal-to-Noise Ratio (SNR)	56 dB
Bit rate range	3 - 8192 Kbit/s
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Number of users	20 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	512 MB
ROM capacity	128 MB
Security	
Alarm input channels	1
Alarm output channels	1
Password protection	Yes
Video motion detection	No
Privacy protection	Yes
Mirror	Yes
Management features	
Web-based management	Yes
Management software	Smart PSS; DSS; DMSS
Power	
Power source type	DC, PoE
Power consumption (typical)	2.7 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

System requirements

Mobile operating systems supported	Android, iOS
------------------------------------	--------------

Weight & dimensions

Height	88.9 mm
--------	---------

Diameter	12.2 cm
----------	---------

Weight	492 g
--------	-------

Packaging data

Package weight	663 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---