

Dahua Technology WizSense 5MP IR Vari-focal Bullet Network Camera

Gamintojas: **DAHUA** · Modelis: **IPC-HFW3541T-ZAS-27135-S2** · EAN: **6923172542373** · Prekės kodas: **666881**



435,90 €

Kaina su PVM

Be PVM: **360,25 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5-MP 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images.
- ✓ Outputs max. 5 MP (2960 × 1668) @20 fps and supports 4MP (2688 × 1520) @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate.
- ✓ Built-in IR LED, max. IR distance: 60 m.
- ✓ ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human).
- ✓ Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.
- ✓ Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); max. 256 G Micro SD card. built-in Mic.
- ✓ 12 VDC/PoE power supply, easy for installation.



Aprašymas

5MP IR Vari-focal Bullet WizSense Network Camera

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	CE-LVD: EN62368-1 CE-EMC: 2014/30/EU FCC: 47 CFR FCC 15, B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
Design	
Mounting type	Ceiling/wall
Product colour	White
Form factor	Bullet
Housing material	Metal
International Protection (IP) code	IP67
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0 lx
Angle of rotation	360°
Lens viewing angle, horizontal	99°
Lens viewing angle, vertical	72°
Lens viewing angle, diagonal	133°
Tilt angle range	0 - 90°
Pan range	0 - 360°
White balance	Auto, Custom modes, Manual, Natural, Outdoor
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Image sensor	
Sensor type	CMOS
Number of sensors	1

Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Focal length range	2.7 - 13.5 mm
Maximum aperture number	1.5
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	60 m
LED type	IR
Number of illumination LEDs	4
Video	
Maximum resolution	2592 x 1944 pixels
Total megapixels	5 MP
Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2592 x 1944
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	3 kbps-8192 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3af

Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; SNMP
Number of users	20 user(s)
Quality of Service (QoS) support	Yes
Streaming method	Multicast

Storage

Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	512 MB
ROM capacity	128 MB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
----------------------------	---

Security

Video motion detection	Yes
Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Mirror	Yes

Power

Power source type	DC, PoE
Power consumption (max)	9.8 W

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	79 mm
Depth	75.9 mm
Length	244.1 mm
Weight	820 g

Packaging data

Package weight	1.09 kg
----------------	---------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (l × P × A)	31,00cm × 16,00cm × 15,00cm
----------------------	-----------------------------