NET CAMERA M3085-V 2MP/02373-001 AXIS

Gamintojas: **AXIS** · Modelis: **02373-001** · EAN: **7331021076631** · Prekės kodas: **666883**



434,90 €

Kaina su PVM

Be PVM: **359,42 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt







Aprašymas

This cost-efficient mini dome features Wide Dynamic Range (WDR) to ensure clarity even when there’s both dark and light areas in the scene. With Lightfinder, it delivers sharp color images even in low light. A deep learning processing unit enables intelligent analytics based on deep learning on the edge. And AXIS Object Analytics offers detection and classification of different types of objects – all tailored to your specific needs. Furthermore, this compact, easy-to-install, vandal-resistant camera comes factory focused so there’s no manual focusing required.

- Built-in cybersecurity features; Compact, discreet design; Great image quality in 2 MP; Support for analytics with deep learning; WDR and Lightfinder

Summary: Axis 02373-001. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 102°, Lens viewing angle, vertical: 55°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Fixed focal length: 3.1 mm | Vendor Homepage: https://www.axis.com/products/axis-m3085-v | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | International Protection (IP) code: IP42 | IK code: IK08 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Lens viewing angle, horizontal: 102 | Lens viewing angle, vertical: 55 | Optical sensor size: 1/2.9 | Sensor type: CMOS | Fixed focal length: 3.1 | Night vision: Yes | Maximum resolution: 1920 x 1080 | Total megapixels: 2 | Video compression formats: H.264H/H.264M/H.265 | Video streaming: Yes | Audio system full duplex: Yes | Ethernet LAN: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Bluetooth: No | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Ethernet LAN (RJ-45) ports: 1 | Motion sensor: Yes | Power source type: PoE | Power consumption (typical): 3.6 | Power consumption (max): 4.2 | Operating temperature (T-T): 0 - 45 | Storage temperature (T-T): -40 - 65 | Operating relative humidity (H-H): 10 - 85 | Storage relative humidity (H-H): 5 - 95 | Height: 56 | Diameter: 101 | Weight: 150 | Number of cameras: 1 | Doesn't contain: BFR/PVC | Unit Calculated Weight: 0.28 | Product Net Weight: 0.25 | Unit Calculated Volume: 0.001188 | Units per Shipping Box: 1 | Unit Width: 11 | Shipping Box

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Height: 9 | Unit Depth: 12 | Unit Height: 9 | Name: NET CAMERA M3085-V 2MP/02373-001 AXIS

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 11,00cm × 9,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903