

Dahua Technology VT03312Q-P video intercom system 2 MP Grey

 Gamintojas: **DAHUA** · Modelis: **VT03312Q-P** · EAN: **6923172532565** · Prekės kodas: **666885**


423,90 €

Kaina su PVM

 Be PVM: **350,33 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full metal casing design
- ✓ Customizable Number of Buttons
- ✓ 1/2.8" 2-MP HD CMOS camera
- ✓ Offers two-way video call with indoor monitors
- ✓ IR illumination and auto WDR
- ✓ Supports two locks
- ✓ Voice call and unlocking through app
- ✓ Two wires and RJ-45 connection
- ✓ IK08 and IP65 rated
- ✓ H.264 and H.265



Aprašymas

- > Full metal casing design.
- > Customizable Number of Buttons (1, 2 or 4 button sets included).
- > 1/2.8" 2-MP HD CMOS camera.
- > Offers two-way video call with indoor monitors.
- > IR illumination and auto WDR.
- > Supports two locks.
- > Voice call and unlocking through app.
- > Two wires and RJ-45 connection.
- > IK08 and IP65 rated.

- > H.264 and H.265.
- > Unlock with IC card.
- > PoE power supply.
- > Included rain cover.
- > Optional red-brown or dark blue front cover.

Vendor Homepage: www.dahuasecurity.com/products/All-Products/Video-Intercoms/2-Wire-Series/Villa-Door-Station/Pro-Series/VT03312Q-P | Audio-In: 1 | Audio-Out: 1 | MicroSD Card Slot: 1 | RJ45: 1 | RS-485: 1 | Alarm In: 1 | Alarm Out: 1 | Shipping Box Height: 8.3 | Unit Calculated Volume: 0.003465 | Units per Shipping Box: 1 | Product Net Weight: 0.57 | Unit Calculated Weight: 0.82 | Power supply requirements: 48 VDC, 1 A | Operating temperature range: -40 °C to +60 °C | Name: ENTRY PANEL 4-BUTTON/VT03312Q-P DAHUA | Dimensions: 188.1 mm × 107.2 mm × 30 mm

Techninė specifikacija

Specifications	
Sandėlio grupė	Door Entry Video Systems [+28][-140]
Features	
Connectivity technology	Wired
Colour	No
Maximum number of cameras supported	1
Speakerphone	Yes
RFID reader	Yes
Door station control	Yes
VoIP protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF
Wall mountable	Yes
Built-in microphone	Yes
Automatic gain control	Yes
Motion detection function	Yes
Display	
Touchscreen	No
Video formats supported	H.264, H.265
Camera	
Megapixel (approx.)	2 MP
Supported video modes	720p, 1080p
Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Maximum frame rate	30 fps
Viewing angle, horizontal	125°
Viewing angle, vertical	65°
Night vision	

Night vision	Yes
LED type	IR
Audio	
Built-in speaker(s)	Yes
Noise-canceling	Yes
Voice codecs	G.711a, G.711u, PCM
Design	
Product colour	Grey
International Protection (IP) code	IP65
IK code	IK08
Housing material	Aluminium
Control type	Buttons
Placement supported	Vertical
Proper use	Outdoor
Storage	
Memory card slot	Yes
Compatible memory cards	MicroSD (TransFlash), SD
Maximum memory card size	256 GB
Network	
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Ethernet LAN (RJ-45) ports	1
Cabling technology	10/100Base-T(X)
Power over Ethernet (PoE)	Yes
Supported network protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF
Power	
Outdoor unit power type	DC
AC adapter output voltage	48 V
AC adapter output current	1 A
Power consumption (typical)	8 W
Power consumption (standby)	4 W
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions	
Width	107.2 mm
Depth	30 mm
Height	188.1 mm
Weight	570 g
Packaging data	
Outdoor unit included	Yes
Package weight	780 g
Technical details	
Compliance certificates	CE, Federal Communications Commission (FCC)
Sustainability compliance	Yes
Logistics data	
Quantity per pack	1 pc(s)
Minimum order quantity	1 pc(s)
Matmenys ir svoris	
Matmenys (l × p × A)	25,00cm × 17,00cm × 8,00cm