

NET CAMERA 5MP BULLET/HFW5559T-ASE-IL-0280B-BK DAHUA

Gamintojas: **DAHUA** · Modelis: **IPC-HFW5559T-ASE-IL-0280B-BLACK** · EAN: **6937552411357** · Prekės kodas: **666889**



408,90 €

Kaina su PVM

Be PVM: **337,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

- High-Quality Imaging with 5MP Resolution
- Xinghan Vision Models: Comprehensive Enhancement of Target Detection, Imaging
- Longer Detection Distance with Xinghan Vision Models
- Supports Over 7 AI Functions, Applicable for Multi-scenario Targets Detection and Analysis
- Built-in Mic for Real-Time Audio Security

Summary: Dahua Technology IPC-HFW5559T-ASE-IL. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Bullet. Minimum illumination: 0.0009 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 108.4°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 61.6 m, Observe distance: 24.6 m, Recognize distance: 12.3 m | Vendor Homepage: <https://www.dahuasecurity.com/products/network-products/network-cameras/wizmind-5-series/smart-dual-light/5mp/ipc-hfw5559t-ase-il> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: Black | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | People counting function: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Built-in light: Yes | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; | Minimum illumination: 0.0009 | Angle of rotation: 360 | Lens viewing angle, horizontal: 108.4 | Lens viewing angle, vertical: 60 | Lens viewing angle, diagonal: 127.1 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter speed: 1/3 - 1/100,000 | Number of Privacy masking areas: 4 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 61.6 | Observe distance: 24.6 | Recognize distance: 12.3 | Focal length range: 2.8 | Fixed focus: Yes | Identify distance: 6.2 | Maximum aperture number: 1.6 | Closest focusing distance: 1 | Night vision: Yes | Night vision distance: 80 | LED type: IR | Maximum resolution: 2960 x 1668 | Total megapixels: 5 | Video compression formats: H.264/H.264B/H.264H/H.265 | Frame rate: 25 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain

control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: H.264: 3 kbps-16384 kbps, H.265: 3 kbps-16384 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: DSS | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Number of microphones: 1 | Voice codecs: G.711a/G.711Mu/G.723/G.726/PCM | Ethernet LAN: Yes | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P; Auto Registration | Wi-Fi: No | Bluetooth: No | Cabling technology: 10/100Base-T(X) | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | ROM capacity: 4000 | RAM capacity: 2000 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Intelligent Video Surveillance (IVS) system features: Face detection/Heat map/Intrusion/People counting/Tripwire | Mirror: Yes | Web browser: Yes | Cloud-managed: No | Power source type: PoE,DC | Power consumption (max): 13.3 | Power consumption (Power over Ethernet (PoE)): 15.6 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Width: 90.7 | Depth: 238 | Height: 90.7 | Weight: 835 | Package weight: 1090 | Package type: Box | Number of cameras: 1 | Audio input: 1 channel (RCA) | Audio output: 1 channel (RCA) | Lens mount interface: M12 | Unit Calculated Weight: 1.06 | Product Net Weight: 0.835 | Unit Calculated Volume: 0.003949 | Units per Shipping Box: 1 | Unit Width: 11.9 | Units per Pallet: 0 | Shipping Box Height: 11.1000003814697 | Unit Depth: 29.9 | Unit Height: 11.1 | Name: NET CAMERA 5MP BULLET/HFW5559T-ASE-IL-0280B-BK DAHUA

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+144][-361]

Matmenys ir svoris

Matmenys (l × p × a)

30,00cm × 12,00cm × 11,00cm