

NET CAMERA 5MP IR BULLET AI/HFW3549T1-AS-PV-0280B-S5 DAHUA

Gamintojas: **DAHUA** · Modelis: **HFW3549T1-AS-PV-0280B-S5** · EAN: **6923172525536** · Prekės kodas: **666892**



402,91 €

Kaina su PVM

Be PVM: **332,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

- 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in warm illuminator, and the max. illumination distance: 40 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing
- Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker
- 12V DC/PoE power supply
- IP67 protection

- SMD Plus
- Red and blue flashlight alarm

Summary: Dahua Technology WizSense IPC-HFW3549T1-AS-PV. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Bullet. Minimum illumination: 0.003 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 98°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 67.4 m, Observe distance: 27 m, Recognize distance: 13.5 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/3-Series/Active-Deterrence/IPC-HFW3549T1-AS-PV> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Certification: CE-LVD: EN62368-1 CE-EMC: 2014/30/EU FCC: 47 CFR FCC 15, B | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.003 | Angle of rotation: 360 | Lens viewing angle, horizontal: 98 | Lens viewing angle, vertical: 71 | Lens viewing angle, diagonal: 129 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Custom modes/Manual/Natural/Outdoor | Camera shutter speed: 1/3 - 1/100000 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 67.4 | Observe distance: 27 | Recognize distance: 13.5 | Identify distance: 6.7 | Maximum aperture number: 1 | Closest focusing distance: 1.2 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 40 | LED type: IR | Maximum resolution: 2592 x 1944 | Total megapixels: 5 | Video compression formats: H.264/H.264+/H.265/H.265+/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440/2592 x 1944/2688 x 1520/640 x 480 (VGA)/704 x 480/704 x 576 | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: 32 - 8192 Kbps, 12 - 8192 Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Built-in microphone: Yes | Voice codecs: AAC/G.711a/G.711Mu/G.723/G.726/PCM | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x/IEEE 802.3af | Supported network protocols: IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Built-in HDD: No | Internal memory: 512 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Intrusion/Tripwire | Mirror: Yes | Video motion detection: Yes | Web-based management: Yes | Power source type: DC,PoE | Power consumption (max): 2 | Power consumption (Power over Ethernet (PoE)): 2.6 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Width: 94.4 | Depth: 84.7 | Length: 288.4 | Weight: 1000 | Package weight: 1230 | Number of cameras: 1 | Unit Calculated Weight: 1.41 | Product Net Weight: 1 | Unit Calculated Volume: 0.008165 | Units per Shipping Box: 8 | Shipping Box Height: 32 | Name: NET CAMERA 5MP IR BULLET AI/HFW3549T1-AS-PV-0280B-S5 DAHUA

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Matmenys ir svoris	
Matmenys (l × p × a)	34,00cm × 15,00cm × 14,00cm