

NET CAMERA 5MP EYEBALL/HDW5559TM-ASE-IL-0360B DAHUA

Gamintojas: DAHUA · Modelis: IPC-HDW5559TM-ASE-IL-0360B · EAN: 6937552410008 · Prekės kodas: 666903



366,90 €

Kaina su PVM

Be PVM: 303,22 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

- 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.
- Outputs max. 5 MP (2960 × 1668) @25/30 fps.
- Built-in multi-core light, the max. IR distance is 50 m and the max. warm light distance is 50 m.
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments.
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- Powered by the Xinghan Large-Scale AI Models-Vision, the camera outstandingly delivers on its object detection, recognition, and scene adaptation functions.
- With deep learning algorithm, it supports: AcuPick, video metadata, IVS, face detection, and people counting, etc.
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 1 TB Micro SD card; built-in Mic
- 12 VDC/PoE power supply; ePoE
- IP67 protection.

Summary: Dahua Technology WizMind IPC-HDW5559TM-ASE-IL. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Turret. Minimum illumination: 0.0005 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 108.4°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 124 m, Observe distance: 49.6 m, Recognize distance: 24.8 m | Vendor Homepage: <https://www.dahuasecurity.com/ceen/products/All-Products/Network-Cameras/WizMind-5-Series/Smart-Dual-Light/5MP/IPC-HDW5559TM-ASE-IL> | Form factor: Turret | Mounting type: Ceiling | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | People counting function: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Dynamic range: 56 | Camera pan control: Yes |

Camera tilt control: Yes | Minimum illumination: 0.0005 | Angle of rotation: 360 | Lens viewing angle, horizontal: 108.4 | Lens viewing angle, vertical: 60 | Lens viewing angle, diagonal: 127.1 | Tilt angle range: 0 - 80 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 124 | Observe distance: 49.6 | Recognize distance: 24.8 | Focal length range: 6 - 2.8 | Fixed focus: Yes | Identify distance: 12.4 | Maximum aperture number: 1.6 | Closest focusing distance: 3.2 | Night vision: Yes | Night vision distance: 50 | LED type: IR/White | Maximum resolution: 2960 x 1668 | Total megapixels: 5 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: G.711 μ -law/G.711 A-law/G.723/G.726/PCM | Built-in microphone: Yes | Ethernet LAN: Yes | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P; Auto Registration | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | ROM capacity: 4000 | RAM capacity: 2000 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Digital watermark: Yes | HTTPS encryption: Yes | Human and vehicle targets classification: Yes | Intelligent Video Surveillance (IVS) system features: Face detection/Heat map/Human detection/Intrusion/People counting/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Cloud-managed: No | Power source type: DC,PoE | Power consumption (typical): 4.2 | Power consumption (max): 13.3 | Power consumption (Power over Ethernet (PoE)): 6.3 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Height: 105.5 | Diameter: 122 | Weight: 530 | Compliance certificates: CE/Electromagnetic Compatibility (EMC) | Package weight: 710 | Package type: Box | Number of cameras: 1 | Manual: Yes | Audio input: RCA | Audio output: RCA | Browser supported: IE: IE 11, Chrome: Chrome 102, Firefox: Firefox 88 | Lens mount interface: M12 | Number of video streams: 4 | Unit Calculated Weight: 0.78 | Product Net Weight: 0.53 | Unit Calculated Volume: 0.00294 | Units per Shipping Box: 1 | Unit Width: 15 | Units per Pallet: 0 | Shipping Box Height: 14 | Unit Depth: 14 | Unit Height: 14 | Name: NET CAMERA 5MP EYEBALL/HDW5559TM-ASE-IL-0360B DAHUA

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+144][-361]

Matmenys ir svoris

Matmenys (l × p × A)

14,00cm × 15,00cm × 14,00cm