

NET CAMERA 4MP PTZ DOME/SD1A404DB-GNY DAHUA

Gamintojas: DAHUA · Modelis: SD1A404DB-GNY · EAN: 6923172590367 · Prekės kodas: 666918



331,90 €

Kaina su PVM

Be PVM: 274,30 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

- 1/2.8" 4Megapixel CMOS
- 4x optical zoom
- Starlight technology
- Max. 25/30 fps@4MP
- IR distance up to 20 m
- Perimeter protection
- Face detection
- SMD 3.0
- Built-in Mic
- IP66; IK08

Summary: Dahua Technology SD1A404DB-GNY. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, White, Form factor: Dome. Minimum illumination: 0.0005 lx, Tilt angle range: 5 - 90°, Tilt preset speed: 0.1 °/sec. Sensor type: CMOS, Optical sensor size: 25.4 / 28 mm (1 / 28"). Signal-to-Noise Ratio (SNR) (panoramic camera): 55 dB | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/PTZ-Cameras/WizSense-Series/SD1/SD1A404DB-GNY> | Form factor: Dome | IK code: IK08 | International Protection (IP) code: IP66 | LED indicators: Yes | Mounting type: Ceiling/wall | Product colour: Black/White | Alarm input/output: Yes | Certification: CE-EMC: EN 55032; EN 61000-3-3; EN 61000-3-2; EN 50130-4; EN 55035 CE-LVD: EN 62368-1 FCC: 47 CFR FCC Part15, Subpart B, NSI C63.4 | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Preset points: Yes | PTZ control: Yes | PTZ modes: 8 Tour/Preset point | PTZ protocols: DH-SD | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Camera pan control: Yes | Camera shutter speed: 1 - 1/30000 | Camera shutter type: Electronic | Camera tilt control: Yes | Minimum illumination: 0.0005 | Pan manual speed: 0.1 - 70 |

Pan preset speed: 0.1 | Pan range: 0 - 355 | Tilt angle range: 5 - 90 | Tilt manual speed: 0.1 - 30 | Tilt preset speed: 0.1 | White balance: Indoor/Manual/Natural/Outdoor/Sodium lamp/Street lamp | Optical sensor size: 1/28 | Progressive scan: Yes | Sensor type: CMOS | Signal-to-Noise Ratio (SNR) (panoramic camera): 55 | Auto focus: Yes | Closest focusing distance: 0.2 | Detect distance (wide): 240 | Digital zoom: 16 | Focal length range: 2.8 - 12 | Focus: Motorized/Manual | Identify distance (wide): 24 | Maximum aperture number: 2.7 | Minimum aperture number: 1.8 | Number of lenses: 1 | Observe distance (wide): 94.8 | Optical zoom: 4 | Recognize distance (wide): 48 | Infra-red LEDs life: 3 | LED type: IR | Night vision: Yes | Night vision distance: 20 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Frame rate: 30 | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Maximum resolution: 2560 x 1440 | Noise reduction: Yes | Noise reduction technology: 2D noise reduction,3D noise reduction | Region of Interest (ROI) encoding: Yes | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Total megapixels: 4 | Video compression formats: H.264/H.264+/H.264B/H.264H/H.265/H.265+/M-JPEG | Video streaming: Yes | Audio detection: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Bluetooth: No | Ethernet LAN: Yes | Number of users: 20 | Supported network protocols: FTP; RTMP; IPv6; Bonjour; IPv4; DNS; RTCP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 512 | RAM capacity: 512 | ROM capacity: 256 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Intelligent Video Surveillance (IVS) system features: Abandoned object/Crossing line/Face detection/Missing object/Tripwire | Video motion detection: Yes | Management software: DMSS; DSS Pro | Web-based management: Yes | Power consumption (max): 13 | Power consumption (typical): 4 | Power source type: DC,PoE | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -30 - 60 | Mobile operating systems supported: Android/iOS | Diameter: 128 | Height: 65.7 | Weight: 500 | Package weight: 700 | Number of cameras: 1 | Product Net Weight: 0.5 | Shipping Box Height: 13.5 | Unit Calculated Volume: 0.003243 | Unit Calculated Weight: 0.74 | Units per Shipping Box: 1 | Model: SD1A404DB-GNY

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+144][-361]

Matmenys ir svoris

Matmenys (I × P × A)

16,00cm × 16,00cm × 14,00cm