

NET CAMERA 5MP IR BULLET/HFW5541T-ASE-0280B-S3 DAHUA

Gamintojas: **DAHUA** · Modelis: **IPC-HFW5541T-ASE-0280B-S3** · EAN: **6923172584335** · Prekės kodas: **666925**



303,90 €

Kaina su PVM

Be PVM: **251,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

Dahua AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, traffic data statistics, etc. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and platform management products. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way

- 1/2.7" 5Megapixel progressive scan CMOS
- H.265&H.264 triple-stream encoding
- 20fps@2592×1944
- WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens (3.6mm, 6mm, 8mm, 12mm optional)
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 78m
- Micro SD memory, IP67

Summary: Dahua Technology Pro DH-IPC-HFW5541T-ASE. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 84°, Lens viewing angle, vertical: 58°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 80 m, Observe distance: 32 m, Recognize distance: 16 m | Vendor Homepage: <https://www.dahuasecurity.com/> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Alarm input/output: Yes | Certification: CE-LVD:EN60950-1 CE-EMC 2014/30/EU FCC:47 CFR FCC 15, B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0 | Angle of rotation: 360 | Lens viewing angle, horizontal: 84 | Lens viewing angle, vertical: 58 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor | Camera shutter type: Electronic/Mechanical | Camera shutter speed: 1/3 - 1/100000 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 80 | Observe distance: 32 | Recognize distance: 16 | Identify distance: 8 | Maximum aperture number: 1.6 | Closest focusing distance: 1.6 |

Fixed focal length: 3.6 | Night vision: Yes | Night vision distance: 78 | LED type: IR | Number of illumination LEDs: 4 | Maximum resolution: 2592 x 1944 | Total megapixels: 5 | Video compression formats: H.264/H.264+/H.265/H.265+/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2592 x 1944/2688 x 1520/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Supported video modes: 1080p/720p | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: 32- 8192Kbps, 19- 8192Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Flip & mirror: Yes | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: AAC | Voice codecs: G.711a/G.711Mu/G.723/G.726 | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP;SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP;QoS; UPnP;NTP | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast/Unicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 512 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Intrusion/People counting/Scene change/Tripwire | Mirror: Yes | Video motion detection: Yes | Web-based management: Yes | Power source type: DC,PoE | Power consumption (max): 7.1 | Power consumption (Power over Ethernet (PoE)): 8.4 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): 5 - 40 | Operating relative humidity (H-H): 10 - 95 | Storage relative humidity (H-H): 10 - 95 | Mobile operating systems supported: Android/iOS | Width: 79 | Depth: 75.9 | Length: 244.1 | Weight: 815 | Package weight: 1080 | Number of cameras: 1 | Unit Calculated Weight: 1.33 | Product Net Weight: 0.82 | Unit Calculated Volume: 0.004742 | Units per Shipping Box: 10 | Unit Width: 12 | Shipping Box Height: 26 | Unit Depth: 30 | Unit Height: 11 | Name: NET CAMERA 5MP IR BULLET/HFW5541T-ASE-0280B-S3 DAHUA | Model: IPC-HFW5541T-ASE-0280B-S3

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Matmenys ir svoris	
Matmenys (l x P x A)	30,00cm x 12,00cm x 11,00cm