

Dahua Technology VTO2202F-P-S3 video intercom system 2 MP Silver

Gamintojas: **DAHUA** · Modelis: **VTO2202F-P-S3** · EAN: **6923172563194** · Prekės kodas: **666926**



286,90 €

Kaina su PVM

Be PVM: **237,11 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Anodized aluminum front panel.
- ✓ CMOS low illumination 2MP HD colorful 168.6° camera.
- ✓ Video intercom function.
- ✓ Provides 12 VDC, 600 mA power.
- ✓ Mobile phone app, talk to the visitor or unlock the door remotely on your phone.
- ✓ IK07 & IP65 rated (silicone sealant is required for the shell, see the quick start guide).
- ✓ Support surface and flush mount.
- ✓ Support H.265 and H.264.
- ✓ Standard PoE power supply (if the VTO device with 12 V power output needs to charge the load, it should be connected to a PSE switch that complies with the 802.3.at standard).



Aprašymas

2-wire IP Villa Door Station

- > Anodized aluminum front panel.
- > CMOS low illumination 2MP HD colorful 168.6° camera.
- > Video intercom function.
- > Provides 12 VDC, 600 mA power.
- > Mobile phone app, talk to the visitor or unlock the door remotely on your phone.

- > IK07 & IP65 rated (silicone sealant is required for the shell, see the quick start guide).
- > Support surface and flush mount.
- > Support H.265 and H.264.
- > Standard PoE power supply (if the VTO device with 12 V power output needs to charge the load, it should be connected to a PSE switch that complies with the 802.3.at standard).

Vendor Homepage: www.dahuasecurity.com/ceen/products/All-Products/Video-Intercoms/2-Wire-IP/Villa-Door-Station/Pro-Series/VTO2202F-P-S3 | RJ45: 1 | RS-485: 1 | Alarm In: 1 | Alarm Out: 1 | Unit Height: 9 | Shipping Box Height: 9 | Unit Depth: 15 | Unit Width: 20 | Units per Pallet: 0 | Unit Calculated Volume: 0.0027 | Units per Shipping Box: 1 | Product Net Weight: 0.35 | Unit Calculated Weight: 0.48 | Model: VTO2202F-P-S3 | Operating temperature range: -30°C to +60°C | Name: ENTRY PANEL IP DOORPHONE/VTO2202F-P-S3 DAHUA | Dimensions: 130 mm × 96 mm × 28.5 mm

Techninė specifikacija

Specifications	
Sandėlio grupė	Door Entry Video Systems [+28][-140]
Features	
Connectivity technology	Wired
Speakerphone	Yes
Door station control	Yes
Streaming capability	Yes
Wall mountable	Yes
Built-in microphone	Yes
Display	
Video formats supported	H.264, H.265
Wide Dynamic Range (WDR)	Yes
Camera	
Megapixel (approx.)	2 MP
Sensor type	CMOS
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Maximum frame rate	25 fps
Field of view (FOV) angle	176.7°
Viewing angle, horizontal	168.6°
Viewing angle, vertical	87.1°
Night vision	
Night vision	Yes
LED type	IR
Audio	
Built-in speaker(s)	Yes

Number of speakers	1
Voice codecs	G.711a, G.711u, PCM
Design	
Product colour	Silver
International Protection (IP) code	IP65
IK code	IK07
Housing material	Aluminium
Control type	Buttons
Placement supported	Vertical
Proper use	Outdoor
Storage	
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Outdoor unit	
RS-485 ports (transmitter)	1
Network	
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Ethernet LAN (RJ-45) ports	1
Cabling technology	10/100Base-T(X)
Power over Ethernet (PoE)	Yes
Supported network protocols	IPv4; RTSP; UDP; DNS; P2P; UPnP; RTP; TCP; SIP
Software	
Operating system installed	Embedded LINUX
Management features	
Web-based management	Yes
Power	
Outdoor unit power type	DC/PoE
Power consumption (typical)	5 W
Power consumption (standby)	4 W
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	96 mm
Depth	28.5 mm
Height	130 mm

Packaging data

Indoor unit included	No
Outdoor unit included	Yes
Package weight	480 g

Technical details

Certification	CE, FCC, UL
---------------	-------------

Logistics data

Quantity per pack	1 pc(s)
-------------------	---------

Matmenys ir svoris

Matmenys (I × P × A)	15,00cm × 20,00cm × 9,00cm
----------------------	----------------------------