

Dahua Technology Lite DH-SD2A500HB-GN-AW-PV-S2 security camera Dome IP security camera Indoor & outdoor 2560 x 1920 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **SDT2A200-2F-NB-A-PV** · EAN: **6939554934919** · Prekės kodas: **666991**



158,90 €

Kaina su PVM

Be PVM: **131,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ · 1/2.8" 5Megapixel STARVIS™ CMOS
- ✓ · Max. 20 fps@5MP
- ✓ · Human detection
- ✓ · Tripwire, intrusion
- ✓ · H.265 encoding
- ✓ · Wi-Fi
- ✓ · Two-way audio
- ✓ · Sound and light alarm
- ✓ · IR and white light, three night view modes
- ✓ · IP66



Aprašymas

The Active Defense series of small PT cameras raises the bar on performance. After detecting an intrusion, it triggers sound and light alarms, and then instantly relays vital information on the intrusion to the mobile client, keeping you informed no matter where you are. It supports two-way talk, allowing you to communicate with people in front of the camera in real time. It also records videos in full color, and uses Smart Dual Light to help produce vivid images, making it easy to obtain information on events, and reduce light pollution.

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
PTZ control	Yes
PTZ modes	Preset sequence
Preset points	Yes
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Built-in light	Yes
Certification	CE: EN55032/EN50130-4/EN IEC61000-3-3/EN IEC61000-3-2/EN55024/EN55035/EN62368-1 FCC: 47 CFR FCC Part15, Subpart B, ANSI C63.4:2014
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Form factor	Dome
International Protection (IP) code	IP66
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0 lx
Lens viewing angle, horizontal	80.4°
Lens viewing angle, vertical	58.1°
Lens viewing angle, diagonal	104.8°
Tilt angle range	0 - 80°
Tilt speed	36.4 °/sec
Tilt preset speed	36.3 °/sec
Pan range	0 - 345°
Pan preset speed	62 °/sec
White balance	ATW, Auto, Indoor, Manual, Outdoor
Camera shutter type	Electronic

Camera shutter speed	1/3 - 1/100000 s
----------------------	------------------

Image sensor

Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes

Lens system

Detect distance	77.4 m
Observe distance	31 m
Recognize distance	15.5 m
Maximum aperture number	1.6
Identify distance	7.74 m
Fixed focal length	4 mm
Closest focusing distance	0.3 m

Night vision

Night vision	Yes
Night vision distance	30 m
LED type	IR

Video

Maximum resolution	2560 x 1920 pixels
Total megapixels	5 MP
Video compression formats	H.264, H.264+, H.264B, H.265, H.265+, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2560 x 1440, 2560 x 1920
Supported video modes	720p, 1080p
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	2D noise reduction, 3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Bit rate	32 Kbps-8192 Kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes

Audio

Built-in speaker(s)	Yes
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711, G.726
Signal-to-Noise Ratio (SNR)	55 dB
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	UDP;FTP;RTMP;IPv6;IPv4;IP Filter;DNS;RTCP;HTTP;NTP;SSL;DHCP;RTP;SMTP;HTTPS;TCP/IP;RTSP;DDNS;ARP
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Number of users	20 user(s)
Streaming method	Multicast, Unicast
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
Internal memory	128 MB
ROM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Management features	
Management software	Smart PSS; DMSS; player; configtool; NVR; Smart Player
Power	
Power source type	DC
Power consumption (typical)	3.5 W
Power consumption (max)	11 W
DC output voltage	12
DC output current	1.5 A
Operational conditions	
Operating temperature (T-T)	-30 - 55 °C
Operating relative humidity (H-H)	0 - 95%

System requirements

Mobile operating systems supported	Android, Windows Mobile, iOS
------------------------------------	------------------------------

Weight & dimensions

Height	140.5 mm
--------	----------

Diameter	11.1 cm
----------	---------

Weight	500 g
--------	-------

Packaging data

Package weight	1 kg
----------------	------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (l × p × a)	19,00cm × 14,00cm × 24,00cm
----------------------	-----------------------------