

Dahua Technology IPC-PT1439H-PV-0280B security camera Dome IP security camera Indoor & outdoor 2560 x 1440 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **IPC-PT1439H-PV-0280B** · EAN: **6939554978883** · Prekės kodas: **666998**



143,91 €

Kaina su PVM

Be PVM: **118,93 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/2.8" 4Megapixel CMOS
- ✓ Max. 25/30 fps@4MP
- ✓ H.265 Encoding
- ✓ Human/Vehicle Detection
- ✓ Perimeter Protection
- ✓ Active Deterrence
- ✓ Smart Dual Light
- ✓ Two-way Talk
- ✓ Easy App Controls



Aprašymas

4MP Smart Dual Light Active Deterrence Network PT Camera

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and mediumsized enterprises.

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cameras [+144][-361]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
PTZ control	Yes
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	EN 62368-1;EN 55032;EN 61000-3-3;EN IEC 61000-3-2;EN 50130-4;EN 55035;
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Form factor	Dome
International Protection (IP) code	IP66
Fog proof	Yes
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.005 lx
Lens viewing angle, horizontal	94°
Lens viewing angle, vertical	51°
Lens viewing angle, diagonal	110°
Tilt angle range	0 - 90°
Pan range	0 - 345°
White balance	Auto, Indoor, Outdoor, Manual, Sodium lamp, Natural, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1 - 1/30000 s
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Lens system	
Focal length range	2.8 - 3.6 mm

Maximum aperture number	1.6
Closest focusing distance	1.2 m
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video compression formats	H.265, H.265+, H.264, H.264+, H.264B, H.264H, H.264M, M-JPEG
Supported graphics resolutions	2560 x 1440, 1920 x 1080 (HD 1080), 1280 x 720 (HD 720), 640 x 360, 320 x 240
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	2D noise reduction, 3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	6 kbps - 8192 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Signal-to-Noise Ratio (SNR)	55 dB
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af
Supported network protocols	HTTP;HTTPS;TCP/IP;IPv4;RTSP;UDP;DHCP;DNS;DDNS;IPv6;SSL;ARP;RTCP;RTP;IP Filter
Storage	
Flash memory	128 MB
Internal memory	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	

Video motion detection	Yes
------------------------	-----

Management features

Management software	Smart PSS;DMSS;Player;ConfigTool;NVR;Smart Player
---------------------	---

Power

Power source type	DC, PoE
-------------------	---------

Power consumption (typical)	3 W
-----------------------------	-----

Power consumption (max)	11 W
-------------------------	------

Power consumption (Power over Ethernet (PoE))	4 W
---	-----

Power consumption (Power over Ethernet (PoE)) (max)	12 W
---	------

DC output voltage	12
-------------------	----

Operational conditions

Operating temperature (T-T)	-30 - 55 °C
-----------------------------	-------------

Weight & dimensions

Height	128.4 mm
--------	----------

Diameter	12.7 cm
----------	---------

Weight	410 g
--------	-------

Packaging data

Package weight	500 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (l × p × A)	17,00cm × 17,00cm × 17,00cm
----------------------	-----------------------------