

WRL ADAPTER 150MBPS PCIE/TL-WN781ND TP-LINK

Gamintojas: **TP-LINK** · Modelis: **TL-WN781ND** · EAN: **6935364050511** · Prekės kodas: **667244**



12,90 €

Kaina su PVM

Be PVM: **10,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

WHAT THIS PRODUCT DOES

TP-LINK TL-WN781N is designed to provide a complete end-to-end wireless performance from the server or server backbone to the switch infrastructure and down through to the desktop with the PCI Express connector. TL-WN781N Wireless Lite N PCI Express(x1) Adapter provides a wider compatibility, fitting with any standard PCI Express slot, x1, x2, x8, or x16. Compared with standard PCI network cards, it offers increased bandwidth, reliability and more functionality, allowing you to enjoy a fast and advanced connection, such as downloading, making internet call and video streaming.

Wireless N ---- Speed & Range

Complying with the IEEE 802.11n standard, TL-WN781N can easily establish a wireless network and get up to 9X the speed and 4X the range of conventional 11g products. Compared with legacy 54M products, TL-WN781N delivers performance enhancements, allowing you to have a more joyful surfing experience, including sharing files, watching streaming media.

WPA / WPA2 Encryptions ---- Advanced Security

As for the security of WI-FI connection, WEP encryption has been no longer the strongest and safest guards for outside intrusions. TL-WN781N provides WPA/WPA2 encryptions that are created by the WI-FI Alliance industry group, preventing the wireless network from outside threats.

Quick Setup Security

Compatible with WI-FI Protected Setup™ (WPS), TL-WN781N features Quick Security Setup (QSS) function, which is ideal for creating a WPA encrypted connection to prevent outside intrusion, and meanwhile maximize the management resources. Not only is this faster than normal security

setups but more convenient in that you don't need to remember a password!

Detachable Antenna

TL-WN781N offers external antenna that can be rotated and adjusted in different directions to fit various operation environments, and can bring better performance than the internal antenna. For even more demanding applications, the antenna can be replaced with diverse antennas to show even greater flexibility and wider wireless coverage.

Features

- Adopts Align™ technology, with transmit speed up to 150Mbps;
- Provides PCI Express connector having a wider compatibility with any standard PCI Express slot;
- Supports QSS function, complying with WPS for worry free wireless security;
- Supports 64/128/152-bit WEP, WPA /WPA2/WPA-PSK/WPA2-PSK(TKIP/AES), supports IEEE 802.1X;
- Supports roaming technology, guaranteeing uninterrupted wireless connection;
- Supports Ad-Hoc/Infrastructure modes;
- Seamlessly compatible with 802.11n/b/g devices;
- Supports Windows 2000, Windows XP 32/64bit, Vista 32/64bit.

- Up to 150Mbps wireless transmission rate
- Provides PCI Express interface
- Advanced secure connection with WPA/WPA2 encryption
- Bundled utility enables easy management

Summary: TP-Link TL-WN781ND. Internal. Connectivity technology: Wireless, Host interface: PCI Express, Interface: WLAN. Maximum data transfer rate: 150 Mbit/s, Wi-Fi band: Single-band (2.4 GHz). Product colour: Green | Vendor Homepage: <https://www.tp-link.com/products/productDetails.asp?class=&pmodel=TL-WN781ND> | Connectivity technology: Wireless | Host interface: PCI Express | Interface:

WLAN | Maximum data transfer rate: 150 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Wi-Fi: Yes | Wi-Fi band: Single-band (2.4 GHz) | Frequency range: 2.4 - 2.4835 | Wi-Fi standards: 802.11b/802.11g | WLAN data transfer rates supported: 11/150/54 | Modulation: 16-QAM/64-QAM/CCK/DBPSK/DQPSK/OFDM | Security algorithms: 128-bit WEP/64-bit WEP/WPA2-PSK/WPA-PSK | Product colour: Green | Internal: Yes | Antenna: Yes | Antenna design: External | Antenna direction type: Omni-directional | Antenna gain level (max): 2 | Chipset: Atheros | Operating modes: Infrastructure mode | Windows operating systems supported: Windows 10/Windows 10 Education/Windows 10 Education x64/Windows 10 Enterprise/Windows 10 Enterprise x64/Windows 10 Home/Windows 10 Home x64/Windows 10 IOT Core/Windows 10 IoT Enterprise/Windows 10 Pro/Windows 10 Pro x64/Windows 10 x64/Windows 7 | Linux operating systems supported: Yes | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 90 | Sustainability compliance: Yes | Width: 120.8 | Depth: 78.5 | Height: 21.5 | Package width: 200 | Package depth: 150 | Package height: 39 | Package weight: 150 | Resource CD: Yes | Quick installation guide: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 0.167 | Product Net Weight: 0.04 | Unit Calculated Volume: 0.00124 | Units per Shipping Box: 1 | Unit Width: 15.5 | Shipping Box Height: 4 | Unit Depth: 20 | Unit Height: 4 | Name: WRL ADAPTER 150MBPS PCIE/TL-WN781ND TP-LINK | Model: TL-WN781ND

Techninė specifikacija

Specifications

Sandėlio grupė

Wireless Network Adapters [+27][-30]

Matmenys ir svoris

Matmenys (I × P × A)

20,00cm × 16,00cm × 4,00cm