

LogiLink NS204 network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Gamintojas: **LOGILINK** · Modelis: **NS204** · EAN: **4052792070460** · Prekės kodas: **667448**



68,90 €

Kaina su PVM

Be PVM: **56,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Industrial switch, 4x 10/100/1000Base-TX + 1x SFP 1000Base-FX
- ✓ Unmanaged, easy installation, plug-and-play
- ✓ Compact and rugged metal housing, IP40
- ✓ Free fall, shock and vibration stability
- ✓ Power input: 12 to 52 V DC redundant power
- ✓ Suitable for DIN-rail mounting
- ✓ Extended operation temperature: -40 °C – +80 °C
- ✓ Suitable power supply: 12 to 52 V (not included)



Aprašymas

The unmanaged Industrial Ethernet switches from LogiLink are particularly suitable for use in harsh environments thanks to the extended temperature range of -40–80 °C. These robust and compact devices enable the connection of several end devices, optionally with power supply via the same Ethernet patch cable (PoE). Due to their flexibility (Giga or Fast Ethernet, with or without PoE) and simplicity (plug-and-play, unmanaged), these switches are not only suitable for industrial applications.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Switches [+2183][-1086]

Management features

Switch typeUnmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	4
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	4
SFP module slots quantity	1

Network

Networking standards	IEEE 802.3z, IEEE 802.3ab, IEEE 802.3u
Full duplex	Yes
Half duplex	Yes

Data transmission

MAC address table	2000 entries
Switching capacity	14 Gbit/s
Forwarding rate	10.5 Mpps

Security

Access Control List (ACL)Yes

Design

Product colour	Black
Housing material	Aluminium
LED indicators	Activity, Link, Power
Wall mountable	Yes

Performance

Mean time between failures (MTBF)300000 h

Power

Power source	DC
Power supply included	Yes
DC input voltage	12 - 52 V
Power consumption (max)	3 W

Operational conditions

Operating temperature (T-T)	-40 - 80 °C
Storage temperature (T-T)	-40 - 80 °C
Storage relative humidity (H-H)	-40 - 80%

Weight & dimensions

Width	118 mm
Depth	86 mm
Height	33.5 mm
Weight	360 g

Packaging content

Manual	Yes
--------	-----

Packaging data

Package type	Box
Package width	165 mm
Package depth	135 mm
Package height	54 mm
Package weight	460 g