

Cudy POE400 PoE adapter Gigabit Ethernet 56 V

Gamintojas: **CUDY** · Modelis: **POE400** · EAN: **6971690791087** · Prekės kodas: **668463**



68,90 €

Kaina su PVM

Be PVM: **56,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ GbE In, GbE Out
- ✓ 100 m (328 ft) Transmission Distance
- ✓ 802.3bt/at/af, Max 90W, 4-Pair
- ✓ Power, PoE Wattage LED
- ✓ Surge/ESD Protection



Aprašymas

Reliable PoE for 24/7 Consistent Operation

IEEE 802.3at/af/bt. Max 90W Output.

The generous 90W power budget easily supports a wide range of devices, including high-power clients like PTZ cameras with heaters, multi-screen kiosks, and advanced access control terminals.

10/100/1000 Mbps Speeds

Stream data at full speed for bandwidth-intensive clients such as access points and AV encoders/decoders with no performance loss.

Exceptional Built-Quality for Stable Operation

Protect Clients with Outstanding EMC

Robust EMC design protects itself and clients from power surges and ESD.

ESD: Contact 6kV; Air 8kV
Surge: Power DM 4kV, CM 4kV; RJ45 CM 4kV

Built to Last Longer with High-Quality Capacitors

Equipped with high-quality capacitors rated for 1.6× longer lifespan than the industry average, making the PoE adapter more resistant to aging and wear.

Easy to Use. Plug and Play.

Auto Negotiating the Power Needed

Connect the power, switches/routers, and clients—the adapter will automatically detect the required power wattage and deliver it accordingly.

Wallmount Ready

Featuring two mounting holes on the back to allow you mount it on the walls.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Cable types supported	Cat5e
Features	
Product colour	Black
Wall mountable	Yes
Plug and Play	Yes
Surge protection	Yes
Maximum operating distance	100 m
LED indicators	PoE, Power
Pin assignment & polarity	1/2 (-), 3/6 (+),4/5 (+), 7/8 (-)
Power protection features	Over current, Over voltage, Overload
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
RJ-45 input ports	1

RJ-45 output ports	1
Power	
Power over Ethernet (PoE) voltage	56 V
Output power	90 W
AC adapter input voltage	100 - 240 V
AC adapter frequency	50 - 60 Hz
Input current	1 A
Operational conditions	
Operating temperature (T-T)	-10 - 45 °C
Operating temperature (T-T)	14 - 113 °F
Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	5 - 80%
Weight & dimensions	
Width	178.5 mm
Depth	80 mm
Height	46 mm
Packaging content	
Number of products included	1 pc(s)
Power cord included	Yes
Packaging data	
Package width	195 mm
Package depth	138 mm
Package height	57 mm