

Canon EOS R50, Black + RF-S 18-45mm F4.5-6.3 IS STM Kit

Gamintojas: **CANON** · Modelis: **5811C035** · EAN: **8714574676050** · Prekės kodas: **673186**



1 219,90 €

Kaina su PVM

Be PVM: **1 008,18 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MILC 24.2 MP CMOS Touchscreen Black
- ✓ TTL Face tracking
- ✓ ISO sensitivity (min): 100 ISO sensitivity (max): 51200 Fastest camera shutter speed: 1/8000 s Slowest camera shutter speed: 30 s ± 3EV (1/3EV step)
- ✓ Video recording 3840 x 2160 pixels 4K Ultra HD
- ✓ Built-in microphone Built-in speaker(s) PictBridge USB Type-C HDMI Bluetooth Wi-Fi
- ✓ Lithium-Ion (Li-Ion)



Aprašymas

Create your best, top performing content with the Canon EOS R50 that shoots professional-looking stills and 4K 30p movies to show off your creativity. Featuring a compact, lightweight design and a large 24.2 megapixel APS-C sized sensor, this EOS R mirrorless all-rounder delivers your passion to your followers in true-to-life quality. Capture more angles than you thought possible due to the flexible Vari-angle touchscreen. When you need to block out distractions, shoot through the electronic viewfinder for the most immersive experience. A great portable camera, the EOS R50's deep learning Dual Pixel CMOS AF II automatically recognises, focusses on and tracks your moving subject, so you never miss a shot. Your creative breakthrough awaits.

Techninė specifikacija

Specifications

Sandėlio grupė Camera > Digital Cameras [+224][-97]

Picture quality

Camera type	MILC
Megapixel (approx.)	24.2 MP
Sensor type	CMOS
Maximum image resolution	6000 x 4000 pixels
Still image resolution(s)	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600
Image stabilizer	No
Image formats supported	JPEG, Raw, C-Raw, HEIF
Image sensor aspect ratio	3:2
Supported aspect ratios	1:1, 3:2, 4:3, 16:9
Image sensor size (W x H)	22.3 x 14.9 mm
Sensor format	Advanced Photo System type-C (APS-C)
Built-in low-pass filter	Yes

Lens system

Focal length range	18 - 45 mm
Minimum focal length (35mm film equiv)	29 mm
Maximum focal length (35mm film equiv)	72 mm
Minimum aperture number	32
Maximum aperture number	4.5
Lens structure (elements/groups)	7/7
Lens type	Standard zoom
Filter size	49 mm
Number of diaphragm blades	7
Lens mount interface	Canon RF

Focusing

Focus	TTL
Focus adjustment	Auto/Manual
Auto focusing (AF) modes	Continuous Auto Focus, One Shot Focus, Servo Auto Focus
Auto Focus (AF) object detection	Animal, Bird, CAT, Dog, People, Vehicle
Face tracking	Yes
Auto Focus (AF) lock	Yes
Auto Focus (AF) assist beam	Yes

Exposure

ISO sensitivity (min)	100
ISO sensitivity (max)	51200
Light exposure modes	Aperture priority AE, Auto, Manual, Shutter priority AE
Light exposure correction	± 3EV (1/3EV step)
Light metering	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot
ISO sensitivity	100, 6400, 25600, 51200
Light exposure control	Program AE
Auto Exposure (AE) lock	Yes
Number of measurement zones	384
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)
Anti-flicker shooting	Yes

Shutter

Fastest camera shutter speed	1/8000 s
Slowest camera shutter speed	30 s
Camera shutter type	Electronic

Flash

Flash exposure lock	Yes
Flash guide number	6 m
External flash connector	Yes
Flash exposure compensation	Yes
Flash exposure correction	±3EV (1/3 EV step)
Shoe mounting point	Yes

Video

Video recording	Yes
Maximum video resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Video resolutions	1920 x 1080, 3840 x 2160 pixels
Video formats supported	H.264, H.265
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit

Audio

Built-in microphone	Yes
Built-in speaker(s)	Yes
Audio system	stereo

Wind filter	Yes
Audio formats supported	LPCM, AAC
Memory	
Compatible memory cards	SD, SDHC, SDXC
Memory slots	1
Display	
Display	LCD
Touchscreen	Yes
Display diagonal (metric)	7.5 cm
Display resolution	1620000 dot
Display aspect ratio	3:2
Vari-angle LCD display	Yes
Viewfinder	
Viewfinder type	Electronic
Magnification	0.95x
Viewfinder screen size	0.39"
Viewfinder frame rate (power saving mode)	60 fps
Viewfinder frame rate (smooth mode)	120 fps
Viewfinder resolution (approx.)	2360000 pixels
Ports & interfaces	
PictBridge	Yes
USB version	2
HDMI	Yes
USB connector	USB Type-C
HDMI version	2
HDMI connector type	Micro
Microphone in	Yes
Network	
Bluetooth	Yes
Wi-Fi	Yes
Bluetooth version	4.2
Bluetooth Low Energy (BLE)	Yes
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Camera	

White balance	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten
Scene modes	Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Panning, Panorama, Portrait, Self-portrait, Silent shutter, Smooth skin, Sports
Shooting modes	Aperture priority, Auto, Intelligent auto, Manual, Program, Scene, Shutter priority
Self-timer delay	2,10 s
Tripod mounting supported	Yes
Dioptre correction	Yes
Diopter adjustment (D-D)	-3 - 1
Histogram	Yes
Live view	Yes
Direct printing	Yes
GPS (satellite)	No
Orientation sensor	Yes
Anti-dust function	No
Smartphone/tablet remote support	Yes
View on smartphone	Yes
Playback zoom (min)	1.5x
Playback zoom number of steps	15
Erase protection options	Folder, Memory card, Single image
Slideshow	Yes
Image processor	DIGIC X

Design

Product colour	Black
Dustproof	No
Splash proof	No

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery type	LP-E17
Number of batteries supported	1
Battery level indicator	Yes
Battery level indicator number of levels	4

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Weight & dimensions

Width	116.3 mm
Depth	68.8 mm
Height	85.5 mm
Weight	328 g
Weight (including battery)	375 g
Lens weight	130 g
Packaging content	
Wrist strap included	Yes
Battery charger included	Yes
Batteries included	Yes
Remote control included	Yes
Carrying case	Yes
Lens cap included	Yes
Logistics data	
Products per pallet	120 pc(s)