

LevelOne TURING 28-Port L3 Lite Managed Gigabit Switch, 24 x 1G RJ45, 4 x 1G/10G SFP+ Uplinks

Gamintojas: **LEVELONE** · Modelis: **GTL-2885** · EAN: **4015867243206** · Prekės kodas: **673865**



1 451,90 €

Kaina su PVM

Be PVM: **1 199,92 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24 Gigabit RJ45 access ports and four 1G/10G SFP+ uplinks provide flexible connectivity for high-bandwidth access and aggregation
- ✓ ERPS (G.8032) support enables sub-50 ms failover in ring topologies, ensuring high network availability for enterprise and campus environments
- ✓ Layer 3 Lite functionality, including IPv4/IPv6 static routing and a built-in DHCP server, improves traffic forwarding efficiency and network segmentation
- ✓ Comprehensive VLAN support, including port-based, protocol-based, Private VLAN, Q-in-Q, and IEEE 802.1Q tagging, allows flexible and secure network segmentation
- ✓ Secure access control with RADIUS and TACACS+ authentication, along with ACL support and multi-level management security
- ✓ Centralized network management through Web UI, SNMP v1/v2c/v3, CLI, Telnet, SSH, and the built-in Device Management System (DMS), which provides management, diagnostics, and monitoring for connected network components and devices.



Aprašymas

The LevelOne GTL-2885 TURING is a 28-port L3 Lite managed Gigabit switch for enterprise and campus networks, featuring 24 Gigabit RJ45 ports and four 1G/10G SFP+ uplinks for flexible access and aggregation. Built-in IPv4/IPv6 static routing, a DHCP server, and ERPS (G.8032) ensure efficient traffic forwarding and high availability.

The integrated Device Management System (DMS) enables centralized control and monitoring of connected devices—including WLAN access points

and IP surveillance—while providing automatic device discovery, security event detection, and cable diagnostics. All management functions are accessible via a standard web browser on PC, tablet, or smartphone.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Management features	
Switch type	Managed
Switch layer	L3
Web-based management	Yes
Traffic classification	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	24
SFP+ module slots quantity	4
Console port	RJ-45
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1x, IEEE 802.1v, IEEE 802.3ad, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3ae, IEEE 802.3z
10G support	Yes
Port mirroring	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, Private VLAN, Voice VLAN, Protocol-based VLAN, MAC address-based VLAN, IP subnet-based VLAN
Number of VLANs	4096
Data transmission	

MAC address table	32000 entries
Switching capacity	128 Gbit/s
Forwarding rate	95.238 Mpps
Static route	Yes
Jumbo frames support	Yes
Jumbo frames	10000
Security	
DHCP features	DHCP server, DHCPv6 server, DHCP relay, DHCP Option 82, DHCP client, DHCPv6 client, DHCP snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
Authentication	Guest VLAN
Authentication type	RADIUS, TACACS+
Multicast features	
Multicast support	Yes
Multicast MAC address table	1024 entries
Multicast Listener Discovery (MLD) snooping	Y
Protocols	
GARP VLAN Registration Protocol (GVRP)	Yes
IP Source Guard (IPSG)	Yes
Design	
Rack mounting	Yes
Product colour	Grey
Performance	
Firmware upgradeable	Yes
Plug and Play	Yes
sFlow	Yes
Fanless	No
Power	
Power source	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	30 W
Power over Ethernet (PoE)	

Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	442 mm
Depth	211 mm
Height	44 mm
Weight	2.67 kg
Packaging content	
Cables included	AC, LAN (RJ-45) to DB9
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Rubber feet	Yes
Package width	520 mm
Package depth	300 mm
Package height	90 mm
Package weight	3.8 kg
Technical details	
Master (outer) cases per pallet (air)	14 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	177.5 cm
Certificates	
Compliance certificates	Low Voltage Directive (LVD), CE, UKCA, RoHS
Logistics data	
Customs product code (TARIC)	8517620000
Country of origin	Taiwan
Master (outer) case width	540 mm
Master (outer) case length	492 mm
Master (outer) case height	326 mm

Master (outer) case gross weight	20 kg
----------------------------------	-------

Products per master (outer) case	5 pc(s)
----------------------------------	---------

Matmenys ir svoris

Svoris	3,78kg
--------	--------