

LevelOne Smart Gigabit RJ45-SFP Media Converter, Compatible with 19-inch rack-mountable chassis

Gamintojas: **LEVELONE** · Modelis: **GVM-2000** · EAN: **4015867243169** · Prekės kodas: **673866**



70,91 €

Kaina su PVM

Be PVM: **58,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1 × 10/100/1000BASE-T RJ45 port and 1 × 100/1000BASE-X SFP port
- ✓ Provides 6 kV surge protection and 6 kV contact / 8 kV air ESD protection
- ✓ Supports QoS, ERPS, IGMP, VLAN, ACL functions
- ✓ Supports management via Web browser and SNMP
- ✓ Fully compatible with 19-inch rack-mountable chassis for easy integration



Aprašymas

The LevelOne GVM-2000 is a Smart Gigabit Media Converter designed to efficiently bridge Ethernet signals between 10/100/1000Base-T and 100/1000Base-X SFP transceiver interfaces. It supports both half- and full-duplex operation and provides versatile fiber connectivity options for flexible deployment in various network environments.

Equipped with an intuitive web-based management interface, the GVM-2000 enables simplified configuration, monitoring, and maintenance—either locally or via SNMP. Users can easily manage key functions such as bandwidth control, duplex mode, port speed, and VLAN configuration. The converter is also compatible with the 19-inch rack-mountable 14-slot Media Converter Chassis (CVH-2000), delivering reliable performance, centralized management, and streamlined network operation.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100Base-T, 1000Base-T
Converter output interface	100Base-X, 1000Base-X
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
VLAN support	Yes
Auto-negotiation	Yes
Quality of Service (QoS) support	Yes
Performance	
Mean time between failures (MTBF)	400000 h
Features	
Internal	No
Web-based management	Yes
LED indicators	Activity, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Output voltage	5 V
Output current	2 A

Power consumption (typical)	19 W
External power adapter	Yes
Weight & dimensions	
Width	94 mm
Depth	71 mm
Height	26 mm
Weight	177 g
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	118 mm
Package depth	78 mm
Package height	86 mm
Package weight	350 g
Package type	Box
Logistics data	
Country of origin	China
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet gross height	154.5 cm
Customs product code (TARIC)	8517620000
Master (outer) case width	500 mm
Master (outer) case length	250 mm
Master (outer) case height	280 mm
Master (outer) case gross weight	13.2 kg
Products per master (outer) case	36 pc(s)