

ATEN 9 x 2 Video Presentation Switch

Gamintojas: **ATEN** · Modelis: **VP1920-AT-G** · EAN: **4719264646089** · Prekės kodas: **674035**



877,90 €

Kaina su PVM

Be PVM: **725,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ VGA port supports universal analog input formats (RGBHV/RGBs/YCbCr/YpPr)
- ✓ Embed/De-embed Audio-HDMI/DisplayPort audio signals can be extracted to digital/analog audio signals; stereo / composite/component audio can be embedded to digital audio signals
- ✓ Superior video quality up to 4096 x 2160@60Hz (4:2:0) / 4096 x 2160@30Hz (4:4:4) (HDMI/DP)
- ✓ EDID Expert - automatically selects the optimum EDID settings for smooth power-up, high-quality display, and the best video resolution across connected devices
- ✓ HDMI (3D, Deep Color, 4K); HDCP 1.4 compliant
- ✓ Multiple control methods via front-panel pushbuttons, RS-232, OSD, and IR remote
- ✓ Source preview - quickly identify and switch to the target content
- ✓ Selectable display modes (Matrix, Mirror, or PiP) for different presentation demands
- ✓ Auto switching - automatically detects and switches to a new source as soon as it is connected for time-saving and convenience
- ✓ Supports stand-by mode for power saving and fast waking up



Aprašymas

The ATEN VP1920 is a 3-in-1 presentation switch that integrates a video matrix switch, an audio processor, and analog-to-digital converter functions. With nine multi-format inputs to two HDMI 4K outputs, it is designed to boost the efficiency and impact of professional presentations.

With streamlined control from front panel pushbuttons, IR remote controller, OSD, and RS-232, the VP1920 reduces not only system device count, but also lower operation complexity. It is suitable for all small-to-medium sized corporate and education presentation environments, such as meeting rooms, classrooms, training rooms, or any other presentation setting, such as in exhibition centers or hotels.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Features	
Product type	Media presentation matrix switcher
Maximum resolution	4096 x 2160 pixels
HDCP	Yes
HDCP version	1.4
3D	Yes
Extended display identification data (EDID)	Yes
Supported resolutions	4096 x 2160, 3840 x 2160, 1920 x 1200
Design	
Housing colour	Black
Housing material	Metal
On/off switch	Yes
LED indicators	Yes
Remote control included	Yes
Display	
Built-in display	No
Ports & interfaces	
HDMI input ports quantity	6
HDMI output ports quantity	2
VGA (D-Sub) input ports	1
DisplayPorts in	1
Digital audio optical out	1
Composite video in	1
USB connector type	USB Type-A, USB Type-B
USB ports quantity	6
RS-232 ports	1
Audio (L/R) out	1
Power	

Power consumption (typical)	7.3 W
AC input voltage	100-240 V
AC input frequency	50-60 Hz
Input current	1 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Heat dissipation	60 BTU/h
Logistics data	
Products per master (outer) case	3 pc(s)
Master (outer) case gross weight	10.3 kg
Master (outer) case length	565 mm
Master (outer) case width	420 mm
Master (outer) case height	258 mm
Master (outer) case net weight	7.5 kg
Harmonized System (HS) code	85299097
Weight & dimensions	
Width	437.2 mm
Depth	163.6 mm
Height	44 mm
Weight	2.5 kg
Package width	131 mm
Package depth	540 mm
Package height	233 mm
Package weight	3.21 kg
Packaging content	
Cables included	AC
Manual	Yes
IR receiver included	Yes